

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
RZN VOR/DME	KAYEK (FB)	275.83 / 30.11	3000	<b>LNAV: RW06</b>  <b>CLIMB TO 3000 DIRECT FTAN AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> HOLD NE, RT, 245.63 INBOUND. CHART FAS OBST: 1334 TOWER 460117N/0925544W CHART VDP AT 1.69 MILES TO RW06. HISMA TO RW06: 3.04/35
KAYEK (IAF)	JASNI (NOPT) (FB)	335.64 / 5.00	3000	
LINDR (IAF)	JASNI (NOPT) (FB)	136.74 / 17.83	3000	
CIVOL (IAF)	JASNI (NOPT) (FB)	050.35 / 14.72	3000	
JASNI (IF/IAF)	HISMA (FB)	065.26 / 6.21	2600	

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD SW JASNI, RT, 065.26 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 065.36 FAF: HISMA DIST FAF TO MAP: 4.79 THLD: 4.79
- MIN. ALT: JASNI 3000, HISMA 2600
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS CLEAR
- MSA FROM: RW06 2700

MAG VAR: 0E EPOCH YEAR: 2010

**MINIMUMS**

TAKEOFF:	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input type="checkbox"/> X										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1600	1	579	1600	1	579		NA			NA				
CIRCLING	1640	1	619	1640	1	619		NA			NA				

NOTES:  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MORA ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET.

SEE 8260-10

CITY AND STATE  HINCKLEY, MN	ELEVATION: 1021 TDZE: 1021	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG  FEB 14 2008	SUP:
	AIRPORT NAME: FIELD OF DREAMS			AMDT: NONE
				DATED

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES CONT.**

**CHART NOTE: VDP NA WHEN USING MORA ALTIMETER SETTING.**

**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RZN VOR/DME VIA V505 AND V13 NORTHEAST BOUND.**

CITY AND STATE <b>HINCKLEY, MN</b>	ELEVATION: 1021 TDZE: 1021 AIRPORT NAME: <b>FIELD OF DREAMS</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 6, ORIG</b>  <b>FEB 14 2008</b>	SUP:
				AMDT: <b>NONE</b>
				DATED:







**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	CIVOL	CIVOL	010	IAF	IF		FB				
	CIVOL	JASNI	020		TF		FB	1.0	050.4 (050T)	014.7	03000
	JASNI	JASNI	010		HF	R	FB		065.3 (065T)	004.0	03000
	LINDR	LINDR	010	IAF	IF		FB				
	LINDR	JASNI	020		TF		FB	1.0	136.7 (137T)	017.8	03000
	RZN	RZN	010		IF		FB				
	RZN	KAYEK	020	IAF	TF		FB	2.0	275.8 (276T)	030.1	03000
	RZN	JASNI	030		TF		FB	1.0	335.6 (336T)	005.0	03000
		JASNI	010	FACF	IF		FB				03000
		HISMA	020	FAF	TF		FB	0.5	065.3 (065T)	006.2	02600
		RW06	030	MAP	TF		FO	0.3	065.4 (065T)	004.8	01055

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	065.4 (065T)		01421
	FITAN	050		DF		FO	1.0			03000
	FITAN	060		HM	R	FO	2.0	245.6 (246T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	RZN	N454913.60	W0922228.30	N4549.227	W09222.472
	CIVOL	N454720.08	W0932432.37	N4547.335	W09324.540
	FITAN	N460605.03	W0923849.96	N4606.084	W09238.833
	HISMA	N455917.93	W0930012.42	N4559.299	W09300.207
	JASNI	N455642.21	W0930818.09	N4556.704	W09308.302
	KAYEK	N455209.04	W0930520.73	N4552.151	W09305.346
	LINDR	N460942.34	W0932548.75	N4609.706	W09325.813
	RW06	N460117.46	W0925357.90	N4601.291	W09253.965

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW06	01020	35

CITY AND STATE  
**HINCKLEY, MN**

ELEVATION: 1021 TDZE: 1021  
AIRPORT NAME:  
**FIELD OF DREAMS**

FACILITY IDENTIFIER:  
**RNAV**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
**RNAV (GPS) RWY 6, ORIG**  
**FEB 14 2008**

SUP:  
AMDT: **NONE**  
DATED:

