

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: FFT VOR					
FINCH/IIU 17.97 DME		FFT VOR			085.08 / 14.04			6000		CLIMB TO 3100 THEN LEFT TURN DIRECT HYK VORTAC AND HOLD, OR AS DIRECTED BY ATC. ALTERNATE MA: CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 3000 DIRECT FFT VOR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 304.00 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD E FFT VOR, RT, 251.21 INBOUND. FAS OBST: 1090 AAO 381253N/0844217W CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 3000 FT FROM THLD.					
1. PT <u>L</u> SIDE OF COURSE <u>071.21</u> OUTBOUND <u>2700</u> FT WITHIN <u>10</u> MILES OF <u>FFT VOR</u> (IAF)										MAG VAR: 3W EPOCH YEAR:1995					
2. _____															
3. FAC <u>251.21</u> FAF _____ DIST FAF TO MAP _____ THLD _____															
4. MIN. ALT _____															
8. MSA FROM: FFT VOR 3100															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-25	1440	3/4	650	1440	3/4	650	1440	1 3/4	650	1440	1 3/4	650			
CIRCLING	1440	1	628	1440	1	628	1440	1 7/8	628	1440	2	628			
NOTES: CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART PLANVIEW NOTE: DME REQUIRED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LEXINGTON ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET, INCREASE S-25 CAT C AND D VISIBILITY 1/4 MILE, AND CIRCLING CAT C (CONTINUED ON PAGE 2)															
CITY AND STATE FRANKFORT, KY		ELEVATION: 812 TDZE: 790 AIRPORT NAME:		CAPITAL CITY		FACILITY IDENTIFIER: FFT		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 25, AMDT 3B 31 MARCH 2016				SUP AMDT 3A DATE 10/16/2014			



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

VISIBILITY 1/8 MILE AND CAT D 1/4 MILE.

CHART NOTE: FOR INOPERATIVE ODALS, INCREASE S-25 CAT C/D VISIBILITY TO 1 7/8 MILES.

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-25 CAT C AND D WHEN USING LEXINGTON ALTIMETER SETTING.



CITY AND STATE

FRANKFORT, KY

ELEVATION: 812

TDZE: 790

AIRPORT NAME:

CAPITAL CITY

FACILITY
IDENTIFIER:

FFT

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 25, AMDT 3B

31 MARCH 2016

SUP:

AMDT: 3A

DATED: 10/16/2014