Federal Aviation Administration

Transmittal Letter 23-19

July 21, 2023

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/7/2023	WI	Crandon	Crandon/Stev e Conway Muni	3/6423	7/14/2023	RNAV (GPS) RWY 30, Orig-A

AIRAC Date: 7 SEPTEMBER 2023

FDC 3/6423 Y55 IAP CRANDON/STEVE CONWAY MUNI, CRANDON, WI. RNAV (GPS) RWY 30, ORIG-A... LPV DA 1958/HAT 311. LNAV/VNAV VIS CATS A/B/C 1. DELETE PROFILE NOTE *LNAV ONLY. DELETE ASTERISK FROM MINIMUM ALTITUDE AT WITKI 2.9 NM TO RW30. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCHGPS. 20:1 IS CLEAR. DELETE NOTE: NIGHT LANDING: RWY 30 NA. CHANGE ALTIMETER NOTE TO READ: USE RHINELANDER ALTIMETER SETTING, WHEN NOT RECEIVED, USE EAGLE RIVER ALTIMETER SETTING AND INCREASE LPV DA TO 1965 FEET; INCREASE LNAV/VNAV DA TO 2012 FEET; INCREASE ALL MDAS 20 FEET. CHANGE HELICOPTER NOTE TO READ: RWY 30 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 30, ORIG-B. 2307141154-PERM