

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SAYKA	DELEO (TF) (FO) (RNP 2.00)	055.50 / 30.19	10200
ECDOL (IAF)	DELEO (NOPT) (TF) (FB) (RNP 1.00)	196.52 / 14.74	10000
DELEO (IF/IAF)	KEFPO (TF) (FB) (RNP 1.00)	247.83 / 8.13	9500
KEFPO	GIBSO (TF) (FB) (RNP 1.00)	247.73 / 3.75	8300
GIBSO (FAF)	RW25 (MAP) (TF) (FO) (RNP 0.30)	247.68 / 6.12	
(SEE FORM 8260-10)			

**LNAV: RW25**

**CLIMBING LEFT TURN TO 11000 DIRECT ADOZO AND HOLD.**

ADDITIONAL FLIGHT DATA:  
HOLD N, LT, 184.47 INBOUND.  
FAS OBST: 6500 AAO 364505N/1042321W  
6740 AAO 364426N/1042114W  
GIBSO TO RW25: 3.00/40.

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD E DELEO, RT, 247.83 INBOUND, 10000 FT. IN LIEU OF PT (IAF)
- FAC: 247.68 FAF: GIBSO DIST FAF TO MAP: 6.12 THLD: 6.12
- MIN. ALT: DELEO 10000, KEFPO 9500, GIBSO 8300
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW25 10900

MAG VAR: 10E EPOCH YEAR: 2000

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	6760	1	422	6760	1	422	6760	1 3/8	422	6760	1 3/8	422			
CIRCLING	6780	1	428	6820	1	468	6820	1 1/2	468	6920	2	568			

NOTES:  
CHART NOTE: CIRCLING NA FOR CAT D WEST OF RWY 2-20.  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SAYKA ON V269-389 SOUTHWEST BOUND.  
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ECDOL ON V263 NORTHEAST BOUND.  
(CONTINUED ON PAGE 2)



CITY AND STATE <b>RATON, NM</b>	ELEVATION: 6352 TDZE: 6338 AIRPORT NAME: <b>RATON MUNI/CREWS FIELD</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMD T NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 25, ORIG-B</b> 22 JUNE 2017	SUP: AMD T: <b>ORIG-A</b> DATED <b>03/05/2015</b>
------------------------------------	--	-------------------------------------	---	---

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW25 (MAP)	6752 MSL (CA)	247.68	
6752 MSL	ADOZO (DF) (FO) (RNP 1.00)		11000

**NOTES, (CONT.):**

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: RWY 2 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.



CITY AND STATE <b>RATON, NM</b>	<b>ELEVATION: 6352</b>	<b>TDZE: 6338</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 25, ORIG-B</b> 22 JUNE 2017	SUP:
	AIRPORT NAME: <b>RATON MUNI/CREWS FIELD</b>				AMDT: <b>ORIG-A</b>
					DATED: <b>03/05/2015</b>