Federal Aviation Administration

Transmittal Letter 19-04

December 28, 2018

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: 						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
31-Jan-19	AR	El Dorado	South Arkansas Rgnl At Goodwin Field	8/0547	12/18/18	ILS OR LOC RWY 22, Amdt 2D

AIRAC Date: 31 JANUARY 2019

FDC **8/0547** ELD IAP SOUTH ARKANSAS RGNL AT GOODWIN FIELD, EI Dorado, AR. ILS OR LOC RWY 22, AMDT 2D... EQUIPMENT REQUIREMENTS NOTE: ADF REQUIRED. NOTE: CIRCLING RWY 4, 13, 31 NA AT NIGHT. DELETE NOTE: NIGHT LANDING: RWY 4, 13,17,31,35 NA. DELETE NOTE: ADF OR DME REQUIRED. DELETE NOTE: ADF REQUIRED. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CAMDEN ALTIMETER SETTING AND INCREASE ALL DA 77 FEET AND ALL MDA 80 FEET. INCREASE S-LOC 22 CAT C AND D VISIBILITY 1/4 MILE. DELETE NOTE: VDP NA WHEN USING CAMDEN ALTIMETER SETTING. CHART NOTE: PROCEDURE NA FOR ARRIVALS ON ELD VOR/DME AIRWAY RADIALS 340 CW 027. THIS IS ILS OR LOC RWY 22, AMDT 2E. 1812131402-PERM