

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> FALLON MUNI	<u>AIRPORT ID</u> KFLX	<u>PROCEDURE NAME</u> RNAV (GPS)-C	<u>ORIGINAL/AMENDMENT</u> ORIG-A	<u>CITY</u> FALLON	<u>STATE</u> NV
<u>AIRPORT ELEVATION</u> 3966	<u>TDZE</u>	<u>SUPERSEDED</u> RNAV (GPS)-C	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>DATED</u> 06/03/2010	<u>MAG VAR</u> 14E
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 20 JUNE 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 2010

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
WADDS	IAF	HZN VORTAC	NOPT	TF	FB	1.00	114.34	19.29	8000
RYANN	IAF	HZN VORTAC	NOPT	TF	FB	1.00	023.64	21.42	8000
HZN VORTAC	IF/IAF	THEMA		TF	FB	1.00	081.03	7.00	6000
THEMA	FAF	MACOG	MAP	TF	FO	0.30	081.12	4.25	
MACOG	MAP	4366 MSL		CA			081.12		
4366 MSL		WADDS		DF	FO	1.00			10100

MISSED APPROACH

MAP:
MACOG

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 10100 DIRECT WADDS AND HOLD, CONTINUE CLIMB-IN-HOLD 10100.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

QUALITY
41
CHECKED

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD W HAZEN VORTAC, LT, 082.00 INBOUND, 8000 FT. IN LIEU OF PT (IAF), MAX 14000.

3. FAC: 081.12

FAF: THEMA

DIST FAF TO MAP: 4.25

DIST FAF TO THLD:

4. MIN ALT: HZN VORTAC 8000, THEMA 6000

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1:

20:1:

TCH:

8. MSA FROM: MACOG 10000

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 13 AND 31.
CHART NOTE: CIRCLING TO RWY 21 NA AT NIGHT.
CHART NOTE: WHEN LOCAL ALTIMETER NOT RECEIVED, USE FALLON NAS ALTIMETER SETTING.

ADDITIONAL FLIGHT DATA:

FAC CROSSES INTERSECTION OF RWYS 3-21 AND 13-31.
CHART R-4803.
CHART FAS OBST: 4266 ANTENNA 392921N/1184510W.
HOLD NW, RT, 114.34 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
CIRCLING	4620	1	654	4620	1	654	4620	1 3/4	654	4620	2	654			

CHANGES - REASONS

1. REMOVED CHART NOTE DME/DME RNP.0.3 NA AND ADDED PBN EQUIPMENT REQUIREMENT NOTES: RNP APCH. - IAW 8260.19H 8-6-8.B.
2. REMOVED "CHART NOTE: CIRCLING TO RWY 13-31 NA AT NIGHT" AND ADDED "CIRCLING NA TO RWY 13 AND 31". - CIRCLING NA TO UNIMPROVED RUNWAY.
3. ADDED CIRCLING RWY 21 NA AT NIGHT. - VISUAL SURFACES PENETRATED.
4. UPDATED REMOTE ALTIMETER NOTE FROM, "USE FALLON NAS ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA." TO "WHEN LOCAL ALTIMETER NOT RECEIVED, USE FALLON NAS ALTIMETER SETTING." - LOCAL ALTIMETER NOW AVAILABLE.
5. UPDATED ALTERNATE MINS FROM NA TO "STANDARD." - LOCAL WEATHER NOW ON FIELD.
6. CHANGED FAS OBST FROM A 4242 MSL TOWER TO 4266 MSL ANTENNA. - NEW CONTROLLING OBSTACLE.



COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZOA, NFL APP CON, AMGR.

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE

DEVELOPED BY

ROBERT G HAMILTON (STEVEN WINNER)

Digitally signed by
CASIMIR L TABAKA

Mar 11, 2019

CASIMIR L TABAKA

Mar 15, 2019

OFFICE

AJV-A422

DATE

01/17/2019

APPROVED BY

JULIE MORGAN

Digitally signed by
CASIMIR L TABAKA

Mar 11, 2019

OFFICE

A42

DATE

TITLE
MANAGER

