

**Federal Aviation
Administration**

Transmittal Letter 21-09

March 9, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/22/2021	VA	Staunton/ Waynesboro/ Harrisonburg	Shenandoah Valley Rgnl	1/6478	2/23/2021	RNAV (GPS) RWY 5, Orig

22 APRIL 2021

FDC 1/6478 SHD IAP SHENANDOAH VALLEY RGNL, STAUNTON/WAYNESBORO/HARRISONBURG, VA. RNAV (GPS) RWY 5, ORIG... DELETE DME/DME RNP-0.3. PBN REQUIREMENTS NOTE: RNP APCH. CHANGE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 46C. CIRCLING CAT A MDA 1660/HAA 459, CAT B MDA 1760/HAA 559, CAT C MDA 1900/HAA 699, CAT D MDA 2060/HAA 859. CIRCLING CAT C VIS 2, CAT D VIS 2 3/4. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLOTTESVILLE ALTIMETER SETTING AND INCREASE ALL DA 130 FEET AND ALL MDA 140 FEET. INCREASE LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS 1/2 SM, LNAV CAT C/D 1/4 SM, CIRCLING CAT C 1/2 SM AND CAT D 1/4 SM. ALTERNATE MINIMUMS STANDARD EXCEPT CAT D 900-2 3/4. NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 5, ORIG-A. 2102221935-PERM