

**Federal Aviation  
Administration**

**Transmittal Letter 22-15**

**MAY 27, 2022**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/14/2022	VT	Highgate	Franklin County State	2/3183	4/28/2022	RNAV (GPS) RWY 1, Amdt 3B

**AIRAC Date: 14 JULY 2022**

FDC 2/3183 FSO IAP FRANKLIN COUNTY STATE, HIGHGATE, VT. RNAV (GPS) RWY 1, AMDT 3B... DELETE  
NOTE: CIRCLING TO RWY 19 NA AT NIGHT. DELETE NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING  
RWY 1 PROCEDURE NA AT NIGHT. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED,  
USE PLATTSBURGH ALTIMETER SETTING AND INCREASE LPV DA TO 576 FEET; LNAV/VNAV DA TO 860  
FEET; INCREASE ALL MDAS 80 FT AND LNAV VISIBILITY CAT B 1/4 SM, AND CIRCLING VISIBILITY CAT B  
1/4 SM. DELETE NOTE: BARO-VNAV NA WHEN USING PLATTSBURGH ALTIMETER SETTING. CHART NOTE:  
PROCEDURE NA AT NIGHT. CHART CIRCLING ICON. THIS IS RNAV (GPS) RWY 1, AMDT 3C. 2203111720-  
PERM