

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 9.11 MILES AFTER RAL VOR							
PDZ VORTAC EDITS INT (IF/IAF)		RAL VOR		046.11 / 4.57				4600		CLIMBING LEFT TURN TO 4500 DIRECT RAL VOR AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4500.							
		RAL VOR (NOPT)		275.21 / 8.45				3900									
ADDITIONAL FLIGHT DATA: HOLD E, RT, 263.86 INBOUND. FAS OBST: 919 AAO 335923N/1173430W RAL VOR TO RW26R: 3.32/53.																	
1. PT <u>R</u> SIDE OF COURSE <u>083.86</u> OUTBOUND <u>4600</u> FT WITHIN <u>10</u> MILES OF <u>RAL VOR</u> (IAF)																	
2.																	
3. FAC <u>263.86</u> FAF RAL VOR DIST FAF TO MAP <u>9.11</u> THLD <u>9.11</u>																	
4. MIN. ALT <u>RAL VOR 3900, HINTN INT 2140*</u>																	
8. MSA FROM: RAL VOR 030-120 11900, 120-295 7000, 295-030 11300																	
MINIMUMS																	
TAKEOFF:		STANDARD		☒		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		☒					
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-26R	2140	1 1/4	1504	2140	1 1/2	1504	2140	3	1504	2140	3	1504					
CIRCLING	2140	1 1/4	1490	2140	1 1/2	1490	2140	3	1490	2140	3	1490					
HINTN FIX MINIMUMS																	
S-26R	1320	1	684	1320	1	684	1320	2	684	1320	2 1/4	684					
CIRCLING	1320	1	670	1320	1	670	1320	2	670	1320	2 1/4	670					
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. *2200 WHEN USING RIVERSIDE MUNI ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RIVERSIDE MUNI ALTIMETER SETTING AND SEE 8260-10																	
CITY AND STATE				ELEVATION: 650 TDZE: 636				FACILITY IDENTIFIER:				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP	
CHINO, CA				AIRPORT NAME:				RAL				VOR RWY 26R, ORIG 22 OCT 2009				AMDT NONE	
				CHINO												DATE	

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

INCREASE ALL MDA 60 FEET, INCREASE HINTN FIX MINIMUMS S-26R AND CIRCLING CAT B, C, AND D
VISIBILITY 1/4 MILE.

CITY AND STATE

CHINO, CA

ELEVATION: 650 TDZE: 636

AIRPORT NAME:

CHINO

FACILITY
IDENTIFIER:
RAL

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 26R, ORIG

22 OCT 2009

SUP:

AMDT: NONE

DATED: