

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
VOR OR TACAN STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.23**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> GUM/PGUM	<u>PROCEDURE NAME</u> VOR OR TACAN RWY 24R	<u>ORIGINAL/AMENDMENT</u> 1C	<u>CITY</u> TAMUNING	<u>STATE</u> GU
<u>AIRPORT ELEVATION</u> 305	<u>TDZE</u> 305	<u>SUPERSEDED</u> VOR OR TACAN RWY 24R	<u>ORIGINAL/AMENDMENT</u> 1B	<u>DATED</u> 01/25/2024
<u>FACILITY</u> UNZ	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 2 OCTOBER 2025	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>MAG VAR</u> 2E
				<u>EPOCH YEAR</u> 2000
				<u>CANCEL/SUSPEND</u>

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
UNZ VORTAC		FIBEE/UNZ 15.58 DME					062.23	15.58	2300
FIBEE/UNZ 15.58 DME	IF/IAF	JUVNI/UNZ 9.57 DME					242.23 (UNZ R-062)	6.01	1800

MISSED APPROACH

MAP:

NOVKE/UNZ 5.11 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2300 THEN LEFT TURN ON UNZ VORTAC R-062 TO FIBEE/UNZ 15.58 DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD NE FIBEE/15.58 DME, LT, 242.23 INBOUND, 2300 IN LIEU OF PT (IAF), MAX 9000.				
3. FAC:	242.23	FAF:	JUVNI/UNZ 9.57 DME	DIST FAF TO MAP:	DIST FAF TO THLD: 4.46
4. MIN ALT:	FIBEE/UNZ 15.58 DME 2300, JUVNI/UNZ 9.57 DME 1800				
8. MSA FROM:	UNZ VORTAC 2600				

EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED.

NOTES:

CHART NOTE: RWY 24R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART NOTE: CIRCLING NA SOUTHEAST OF RWY 6R-24L.

ADDITIONAL FLIGHT DATA:

JUVNI TO RW24R: 3.00/75.
CHART FAS OBST: 865 TOWER (GU-000243) 132914N/1444948E.
CHART VDP AT 7.61 DME.
DISTANCE VDP TO THLD 2.49 NM.
CHART CIRCLING ICON.



MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT
ALTERNATE: NA ☐ CAT A, B 900-2, CAT C, D 900-2 1/2

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-24R	1180	1	875	1180	1 1/4	875	1180	2 1/2	875	1180	2 1/2	875			
CIRCLING	1180	1 1/4	875	1180	1 1/4	875	1180	2 1/2	875		NA				

CHANGES - REASONS
1.LOCATION IDENTIFIER: CHANGED LOCATION IDENTIFIER FROM GUAM TO TAMUNING - 28 DAY TRACKER REVIEW #27520.

COORDINATED WITH:
A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:** GUAM CERAP, AGANA ATCT, AMGR

FLIGHT CHECKED BY
PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

Digitally signed by

RAKE MCGRAW

Jul 01, 2025

OFFICE

DATE

DEVELOPED BY
JANTZEN TAYLOR

Digitally signed by

JANTZEN L TAYLOR

Jun 17, 2025

OFFICE
AJV-A422

DATE
02/05/2025

APPROVED BY
RAKE MCGRAW

Digitally signed by

RAKE MCGRAW

Jul 01, 2025

OFFICE
AJV-A422

DATE

TITLE
MANAGER

