

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
GDM VOR/DME	LAWRN/GDM 23.00 DME	167.26 / 23.00	3000	MAP: GDM 19.01 DME FIX
PUT VOR/DME (IAF)	SQUEL/GDM 29.00 DME (NOPT)	034.17 / 10.12	3000	CLIMBING LEFT TURN TO 3000 ON HEADING 240 AND GDM VOR/DME R-191 TO GRAYM INT/GDM 26.70 DME AND HOLD.
SQUEL/GDM 29.00 DME (IF)	LAWRN/GDM 23.00 DME	347.26 / 6.00 (GDM R-167)	2500	
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 191.44 INBOUND. CHART FAS OBST: 1210 TOWER 421327N/0715252W LAWRN TO RW33: 3.45/40.

1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
2. HOLD S LAWRN, LT, 347.26 INBOUND, 2700 FT. IN LIEU OF PT (IAF)
3. FAC 347.26 FAF LAWRN/GDM 23.00 DME DIST FAF TO MAP _____ THLD 3.99
4. MIN. ALT LAWRN 2500
8. MSA FROM: GDM VOR/DME 330-060 4400, 060-330 3300

MAG VAR: 14W EPOCH YEAR: 1970

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			STANDARD @					
CATEGORY ==>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-33	1520	1	522	1520	1	522	1520	1 1/2	522	1520	1 1/2	522			
CIRCLING	1560	1	551	1640	1	631	1720	2	711	1980	3	971			

NOTES:
 CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 33 PROCEDURE NA AT NIGHT.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEDFORD ALTIMETER SETTING AND INCREASE (SEE FORM 8260-10)

@ CAT D 1000-3
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE WORCESTER, MA	ELEVATION: 1009	THRE: 998	FACILITY IDENTIFIER: GDM	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 33, AMDT 1A 18 OCTOBER 2012	SUP
	AIRPORT NAME: WORCESTER RGNL				AMDT 1
					DATE 08/23/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

ALL MDA 200 FEET; INCREASE S-33 CAT C/D VISIBILITY 1/2 MILE AND CIRCLING CAT C VISIBILITY 3/4 MILE.

CITY AND STATE

WORCESTER, MA

ELEVATION: 1009

THRE: 998

AIRPORT NAME:

WORCESTER RGNL

FACILITY
IDENTIFIER:

GDM

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME RWY 33, AMDT 1A

18 OCTOBER 2012

SUP:

AMDT:

1

DATED:

08/23/2012