

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> FRANKLIN COUNTY	<u>AIRPORT ID</u> F53	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 31	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>CITY</u> MOUNT VERNON	<u>STATE</u> TX	
<u>AIRPORT ELEVATION</u> 412	<u>TDZE</u> 412	<u>SUPERSEDED</u> RNAV (GPS) RWY 31	<u>ORIGINAL/AMENDMENT</u> ORIG-A	<u>DATED</u> 11/12/2015	<u>MAG VAR</u> 6E	<u>EPOCH YEAR</u> 1985
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 21 MAY 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
JAXAB		GEBCE		TF	FB	1.00	127.96	17.85	3000
GEBCE	IAF	FOSMA		TF	FB	1.00	040.51	5.00	3000
HEBIP	IAF	FOSMA		TF	FB	1.00	257.55	7.26	3000
FOSMA	IF	CIPNI		TF	FB	1.00	310.55	6.20	2000
CIPNI	FAF	RW31	MAP	TF	FO	0.30	310.54	4.78	
RW31	MAP	812 MSL		CA			310.54		
812 MSL		FOSMA		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LNAV: RW31

MISSED APPROACH INSTRUCTIONS:

CLIMBING RIGHT TURN TO 3000 DIRECT FOSMA AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. PROFILE STARTS AT FOSMA

3. FAC: 310.54

FAF: CIPNI

DIST FAF TO MAP: 4.80

DIST FAF TO THLD: 4.80

4. MIN ALT: FOSMA 3000, CIPNI 2000

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1: IS NOT CLEAR

20:1: IS CLEAR

TCH:

8. MSA FROM: RW31 2600

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING RWY 13 NA AT NIGHT.
CHART NOTE: RWY 31 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HEBIP ON V54 NORTHEAST BOUND.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JAXAB ON V573 SOUTHWEST BOUND AND ON V583 NORTHBOUND.
CHART NOTE: USE MOUT PLEASANT RGNL ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA.

ADDITIONAL FLIGHT DATA:

CHART MOUNT PLEASANT RGNL AWOS-3.
CIPNI TO RW31: 3.05/40.
CHART FAS OBST: 780 TOWER 331101N/0951233W.
HOLD SE, RT, 310.55 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	1160	1	748	1160	1 1/4	748		NA			NA				
CIRCLING	1160	1	748	1160	1 1/4	748		NA			NA				



