

**Federal Aviation
Administration**

Transmittal Letter 20-21

August 21, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/8/2020	ME	Augusta	Augusta State	0/4432	7/29/2020	ILS OR LOC RWY 17, Amct 3B

AIRAC Date: 8 OCTOBER 2020

FDC 0/4432 AUG IAP AUGUSTA STATE, AUGUSTA, ME. ILS OR LOC RWY 17, AMDT 3B...
CHART CIRCLING ICON. CIRCLING CAT A MDA 940/HAA 588, CAT D MDA 1160/HAA 808.
VIS CAT D 2 1/2. SHAWEE FIX MINIMUMS: CIRCLING CAT A MDA 940/HAA 588, CAT D MDA
1160/HAA 808. VIS CAT D 2 1/2. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 900-2
1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE WATERVILLE ALTIMETER SETTING;
INCREASE S-ILS 17 DA TO 583; INCREASE ALL MDAS 40 FT AND S-LOC 17 CAT C/D
VISIBILITY 1/8 MILE; SHAWEE FIX MINIMUMS INCREASE S-LOC 17 CAT C/D VISIBILITY 1/8
MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
WATERVILLE ALTIMETER SETTING: INCREASE S-ILS 17 DA TO 583; INCREASE ALL MDAS
40 FT AND VISIBILITY S-LOC 17 CAT C AND D 1/8 SM, AND CIRCLING CAT D 1/4 SM;
SHAWEE FIX MINIMUMS INCREASE S-LOC 17 CAT C AND D VISIBILITY 1/8 SM, AND
CIRCLING CAT D VISIBILITY 1/4 SM. THIS IS ILS OR LOC RWY 17, AMDT 3C. 2007241437-
PERM