

**Federal Aviation
Administration**

Transmittal Letter 21-09

March 9, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/22/2021	OH	Bellefontaine	Bellefontaine Rgnl	1/9057	3/2/2021	RNAV (GPS) RWY 7, Amdt 1A

22 APRIL 2021

FDC 1/9057 EDJ IAP BELLEFONTAINE RGNL, BELLEFONTAINE, OH. RNAV (GPS) RWY 7, AMDT 1A... CIRCLING CAT C MDA 1860/HAA 738, CAT D MDA 1980/HAA 858. CIRCLING VIS CAT C 2, CAT D 2 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JAMES M. COX DAYTON INTL ALTIMETER SETTING; INCREASE LPV DA TO 1456 FEET, LNAV/VNAV DA TO 1598 FEET, AND ALL MDAS 100 FEET, AND INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 SM, LNAV CATS C AND D VISIBILITY 3/8 SM, AND CIRCLING CAT C VISIBILITY 1/2 SM AND CAT D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 7, AMDT 1B. 2103011352-PERM