

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW26
BRV VORTAC	MILHI (FB)	209.87 / 12.18	4000	CLIMB TO 3000 DIRECT STPBV AND HOLD.
RIC VORTAC	BUDYY (FB)	001.00 / 25.00	3000	
MILHI (IAF)	SHLBE (FB)	209.82 / 8.00	3000	ADDITIONAL FLIGHT DATA: HOLD W, RT, 084.49 INBOUND. FAS OBST: 539 AAO 375758N/0774207W CHART HILL MOA. CHART: LOUISA COUNTY/FREEMAN FIELD AWOS HHANK TO RW26: 3.00/40
BUDYY (IAF)	SHLBE (FB)	334.49 / 7.75	3000	
SHLBE (IF)	HHANK (FB)	264.79 / 6.95	2000	
HHANK (FAF)	RW26 (MAP) (FO)	264.70 / 5.05		
RW26 (MAP)	751 MSL	264.70		
751 MSL	STPBV (FO)		3000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT SHLBE
- FAC: 264.70 FAF: HHANK DIST FAF TO MAP: 5.05 THLD: 5.05
- MIN. ALT: SHLBE 3000, HHANK 2000
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW26 3100

MAG VAR: 10W EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY ==>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1360	3	1009	1360	3	1009		NA			NA					
CIRCLING	1360	3	1009	1360	3	1009		NA			NA					

NOTES:
 CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON BRV VORTAC AIRWAY RADIALS 141 CW 214.
 (SEE FORM 8260-10)



CITY AND STATE BUMPASS, VA	ELEVATION: 351 THRE: 351 AIRPORT NAME: LAKE ANNA	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, ORIG 15 DEC 2011	SUP: AMDT: NONE DATED
-------------------------------	---	------------------------------	--	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON RIC VORTAC AIRWAY RADIALS 283 CW 048.

CHART NOTE: USE LOUISA COUNTY/FREEMAN FIELD ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA.



CITY AND STATE BUMPASS, VA	ELEVATION: 351 THRE: 351	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, ORIG 15 DEC 2011	SUP:
	AIRPORT NAME: LAKE ANNA			AMDT: NONE
	DATED:			

