

**FEDERAL AVIATION ADMINISTRATION  
 FLIGHT STANDARDS SERVICE  
 ILS STANDARD INSTRUMENT APPROACH PROCEDURE  
 TITLE 14 CFR PART 97.29**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.  
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u><b>AIRPORT ID</b></u> KSLC	<u><b>PROCEDURE NAME</b></u> ILS OR LOC RWY 34L ILS RWY 34L (SA CAT I), ILS RWY 34L (CAT II), ILS RWY 34L (CAT III)	<u><b>ORIGINAL/AMENDMENT</b></u> 3E	<u><b>CITY</b></u> SALT LAKE CITY	<u><b>STATE</b></u> UT	
<u><b>AIRPORT ELEVATION</b></u> 4231	<u><b>TDZE</b></u> 4229	<u><b>SUPERSEDED</b></u> ILS OR LOC RWY 34L ILS RWY 34L (SA CAT I), ILS RWY 34L (CAT II), ILS RWY 34L (CAT III)	<u><b>ORIGINAL/AMENDMENT</b></u> 3D	<u><b>DATED</b></u> 11/08/2018	<u><b>MAG VAR</b></u> 11E
<u><b>FACILITY</b></u> I-UUH	<u><b>COORDINATES OF FACILITIES</b></u>	<u><b>ACTUAL EFFECTIVE DATE</b></u> 22 APRIL 2021	<u><b>REQUIRED EFFECTIVE DATE</b></u> ROUTINE	<u><b>CANCEL/SUSPEND</b></u>	<u><b>EPOCH YEAR</b></u> 2020

**TERMINAL ROUTES**

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
FFU VORTAC	IAF	PUTER/I-UUH 20.28 DME/RADAR					339.74	9.64	10000
PUTER/I-UUH 20.28 DME/RADAR	IAF	CAMRI/I-UUH 17.91 DME/RADAR					343.95	2.37 (I-UUH)	9000
CAMRI/I-UUH 17.91 DME/RADAR	IF	DUNLP/I-UUH 14.75 DME/RADAR					343.95	3.16 (I-UUH)	8000
DUNLP/I-UUH 14.75 DME/RADAR		FLLAG/I-UUH 5.54 DME/RADAR					343.95	9.21 (I-UUH)	6100

**MISSED APPROACH**

**MAP:**

ILS: DA  
 LOC: 5.26 NM AFTER FLLAG/I-UUH 5.54 DME/RADAR OR AT FALEM/I-UUH 0.29 DME FIX

**MISSED APPROACH INSTRUCTIONS:**

CLIMB TO 4800 THEN CLIMBING LEFT TURN TO 8100 ON TCH VORTAC R-249 TO STACO INT/TCH 20.00 DME AND HOLD.

**ALTERNATE MISSED APPROACH INSTRUCTIONS (DO NOT CHART):**

CLIMB TO 4800 THEN CLIMBING LEFT TURN TO 10000 ON HEADING 260, EXPECT RADAR VECTORS. (RADAR REQUIRED).



**AIRPORT ID**  
KSLC

**PROCEDURE NAME**  
ILS OR LOC RWY 34L  
ILS RWY 34L (SA CAT I),  
ILS RWY 34L (CAT II),  
ILS RWY 34L (CAT III)

**ORIGINAL/AMENDMENT**  
3E

**CITY**  
SALT LAKE CITY

**STATE**  
UT

**PROFILE:**

- 1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- 2. PROFILE STARTS AT PUTER
- 3. FAC: 343.95 FAF: FLLAG/I-UUH 5.54 DME/RADAR DIST FAF TO MAP: 5.26 DIST FAF TO THLD: 5.71
- 4. MIN ALT: PUTER/I-UUH 20.28 DME/RADAR 10000, CAMRI/I-UUH 17.91 DME/RADAR 9000, DUNLP/I-UUH 14.75 DME/RADAR 8000, FLLAG/I-UUH 5.54 DME/RADAR 6100, JUGOX/I-UUH 1.43 DME/RADAR 4780\*
- 5. DIST TO THLD FROM OM: MM: IM: 100 HAT: 866 150 HAT: 1820 GS ANT: 1051
- 6. MIN GS INCPT: 6100 GS ALT AT FAF : FLLAG/I-UUH 5.54 DME/RADAR 6100 OM: MM: IM:
- 7. GP ANGLE: 3.00 34:1 20:1 TCH: 54.6
- 8. MSA FROM: TCH VORTAC 050-230 12700, 230-320 8600, 320-050 11000

**EQUIPMENT REQUIREMENTS NOTES:**

RADAR REQUIRED FOR ARRIVALS AT PUTER.  
DME OR RADAR REQUIRED.

**NOTES:**

SA CAT I ILS - SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED; S-ILS 34L: CAT A, B, C, D RA 158, RVR 1400, HAT 150, DA 4379 MSL.  
 CAT II ILS - SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED; S-ILS 34L: CAT A, B, C, D RA 102, RVR 1200, HAT 100, DA 4329 MSL.  
 CAT III ILS - SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED; S-ILS 34L: CAT A, B, C, D RVR 300  
 CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED.  
 SA CAT I CHART NOTE: REQUIRES SPECIFIC OPSPEC, MSPEC, OR LOA APPROVAL AND USE OF HUD TO DH.  
 CAT II RVR 1000 CHART NOTE: RVR 1000 AUTHORIZED WITH SPECIFIC OPSPEC, MSPEC, OR LOA APPROVAL AND USE OF AUTOLAND OR HUD TO TOUCHDOWN.  
 CHART PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).  
 \*LOC ONLY  
 CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 34L CAT C/D VISIBILITY TO RVR 6000

**ADDITIONAL FLIGHT DATA:**

HOLD W, LT, 069.32 INBOUND.  
 CHART FAS OBST: 4374 POLE 404437N/1115917W.  
 4660 AAO 404016N/1120000W.  
 CHART R-6412 A/B/C/D.  
 CHART VDP AT 0.89 DME\*  
 DISTANCE VDP TO THLD 1.06 NM.  
 \*LOC ONLY.

**MINIMUMS:**

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

**ALTERNATE:** NA  ILS: STANDARD; LOC: STANDARD

CATEGORY:	A			B			C			D			E		
	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-ILS 34L	4429	1800	200	4429	1800	200	4429	1800	200	4429	1800	200			
S-LOC 34L	4640	2400	411	4640	2400	411	4640	4000	411	4640	4000	411			

QUALITY  
16  
CHECKED

**CHANGES - REASONS**

1. AIRPORT ELEVATION CHANGED FROM 4227 FT TO 4231 FT AND TDZE CHANGED FROM 4226FT TO 4229 FT - NEW AIRPORT SURVEY.
2. SA CAT I ILS DA CHANGED FROM 4376 FT TO 4379 FT - TDZE INCREASED 3 FT.
3. SAT CAT II ILS DA CHANGED FROM 4326 FT TO 4329 FT - TDZE INCREASED 3 FT.
4. CHART FAST OBST: CHANGED FROM 4279 TREE 404542N/1115954W TO 4374 POLE 404437N/1115917W - NEW CONTROLLING OBS..
5. ADDED VDP INFORMATION: CHART VDP AT 0.89 DME\* AND DISTANCE VDP TO THLD 1.06 NM - MDA INCREASED, MAP MORE THEN 0.5 NM BEFORE MAP.
6. S-ILS 34L DA CHANGED FROM 4426 FT TO 4429 FT - TDZE INCREASED 3 FT.
7. S-LOC 34L MDA/HAT CHANGED FROM 4560/334 TO 4640/411 - NEW CONTROLLING OBS
8. S-LOC 34L CAT C/D VIS CHANGED FROM RVR 2600 FT TO RVR 4000 FT - PER 8260.3D VISIBILITY TABLES CHAPTER 3.
9. NOTES: CHANGED CAT III ILS - SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED; S-ILS 34L: CAT III CAT A, B, C, D RVR 700, CAT IIIB CAT A, B, C, D RVR 300. CAT IIIC NA TO SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED; S-ILS 34L: CAT III CAT A, B, C, D RVR 300 - PER 8260.19H 8-6-11M/8400.13D.
10. ADDED INOPERATIVE NOTE FOR S-LOC 34L CAT C/D - PER 8260.3D VISIBILITY TABLES CHAPTER 3.

**COORDINATED WITH:**

**A4A**  **ALPA**  **AOPA**  **APA**  **HAI**  **NBAA**  **OTHER:** ZLC, ATCT, UT AERO, AMGR

**FLIGHT CHECKED BY**

JORDAN ROLIH

*Digitally signed by*  
**DONALD H LANIER**

Nov 24, 2020

**OFFICE**

FICO

**DATE**

11/21/2020

**DEVELOPED BY**

TARA MARTINELLI

*Digitally signed by*  
**TARA N MARTINELLI**

Sep 14, 2020

**OFFICE**

AJV-A431

**DATE**

09/14/2020

**APPROVED BY**

LONNIE EVERHART

*Digitally signed by*  
**DONALD H LANIER**

Nov 24, 2020

**OFFICE**

AJV-A430

**DATE**

**TITLE**  
MANAGER

