

**Federal Aviation  
Administration**

**Transmittal Letter 19-17**

**June 28, 2019**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	ND	Linton	Linton Muni	9/0821	6/25/2019	RNAV (GPS) RWY 27, Orig-B

**AIRAC Date: 15 AUGUST 2019**

FDC 9/0821 7L2 IAP LINTON MUNI, Linton, ND. RNAV (GPS) RWY 27, ORIG-B... DELETE CIRCLING MINIMUMS. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C OR ABOVE 54C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 54C (130F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BISMARCK MUNI ALTIMETER SETTING AND INCREASE ALL DA 107 FEET AND VISIBILITY LPV AND LNAV/VNAV ALL CATS 1/4 SM; INCREASE ALL MDA 120 FEET AND VISIBILITY LNAV CAT C 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BISMARCK MUNI ALTIMETER SETTING AND INCREASE ALL DA 107 FEET AND VISIBILITY LPV AND LNAV/VNAV 1/4 MILE ALL CATS; INCREASE ALL MDA 120 FEET AND VISIBILITY LNAV CAT C AND CIRCLING CAT C 1/4 MILE. THIS IS RNAV (GPS) RWY 27, ORIG-C. 1906241311-PERM