

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
BIHSU (IAF) (40E) (43A)	OJEFY (NoPT) (TF)(FB) (40E)(41E)	085.87/5.01	3000	LNAV: CERIV											
UYUDE (IAF) (40E) (43A)	OJEFY (NoPT) (TF (FB) (40E)(41E)	265.99/5.01	3000	CLIMB TO 3000 DIRECT UNHAF AND HOLD											
OJEFY (IF/IAF) (40E) (43I)	UGEKY (TF) (FB) (40E) (43F)	355.93/6.01	2700												
CERIV (MAP) (40G) (41Y) (43M)	1230 MSL (CA) (42M)	355.93													
1230 MSL	UNHAF (DF) (FO) (40E) (41E) (43H)		3000	ADDITIONAL FLIGHT DATA: HOLD N, RT, 175.93 INBOUND FAS OBST: 1029 TREE 363503N / 0944342W 1079 TREE 363137N / 0944311W CHART 1159 TREE 363004N / 0944321W											
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)				UGEKY TO RW36: 3.05/40											
2. HOLD S OJEFY, RT, 355.93 INBOUND, 3000 FT IN LIEU OF PT (IAF) (40E) (41E) (43C)				CHART VDP AT 0.96 MILES TO CERIV											
3. FAC: 355.93 FAF: UGEKY DIST FAF TO MAP: 5.17 THLD: 5.66				ROUTE TYPE DESCRIPTION: A, P											
4. MIN. ALT: OJEFY 3000, UGEKY 2700, GOTYE/3.38NM TO CERIV (40E) (42S) 2120				APPROACH ROUTE QUALIFIER 2: S											
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS CLEAR															
8. MSA FROM: _____				MAG VAR: 4E EPOCH YEAR: 00											
MINIMUMS															
TAKEOFF:	X	STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD										
CATEGORY =====>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1280	1	450	1280	1	450	1280	1 1/4	450		NA				
CIRCLING	1500	1	670	1500	1	670	1500	1 3/4	670		NA				
NOTES: CHART NOTE: DME/DME RNP -0.3 NA															
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT															
CITY AND STATE		ELEVATION: 830 TDZE: 830		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:					
GROVE, OK		GROVE MUNI		RNAV		MAY 12 2005 RNAV (GPS) RWY 36, ORIG				AMDT: NONE					
										DATE					

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES CONT:

	FROM	TO	ALTITUDE
1.	266/30 CW 086/30	266/20 CW 086/20	3100
2.	266/20 CW 086/20	OJEFY (IF/IAF) (NoPT)	3000
3.	086/30 CW 176/30	BIHSU (IAF)	3000
4.	176/30 CW 266/30	176/25 CW 266/25	3100
5.	176/25 CW 266/25	UYUDE (IAF)	3000

CITY AND STATE

GROVE, OK

ELEVATION:

830 TDZE:

830

AIRPORT NAME:

GROVE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

MAY 12 2005
RNAV (GPS) RWY 36, ORIG

SUP:

AMDT: NONE

DATED: