

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW08
RUJAP (IAF)	SEPBU (NOPT) (FB)	166.86 / 5.00	5000	CLIMB TO 5000 DIRECT NEGVE AND HOLD.
TAULS (IAF)	SEPBU (NOPT) (FB)	346.90 / 5.00	5000	
SEPBU (IF/IAF)	UBIRE (FB)	076.88 / 6.53	3800	ADDITIONAL FLIGHT DATA: HOLD E, RT, 257.19 INBOUND. FAS OBST: 2149 AAO 373927N/0821226W CHART PINEVILLE AWOS-3 UBIRE TO RW08: 3.05/40.
UBIRE (FAF)	RW08 (MAP) (FO)	076.96 / 5.97		
RW08 (MAP)	2282 MSL	076.96		
2282 MSL	NEGVE (FO)		5000	

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD W SEPBU, RT, 076.88 INBOUND, 5000 FT. IN LIEU OF PT (IAF)
3. FAC: 076.96 FAF: UBIRE DIST FAF TO MAP: 5.97 THLD: 5.97
4. MIN. ALT: SEPBU 5000, UBIRE 3800
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
7. GS ANGLE:        TCH: 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 7W EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X				
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2580	1	754	2580	1 1/4	754	2580	2	754	2580	2	754			
CIRCLING	2680	1	798	2680	1 1/4	798	2680	2 1/4	798	2720	2 3/4	838			

NOTES:  
CHART NOTE: USE PINEVILLE ALTIMETER SETTING; WHEN NOT RECEIVED, USE BECKLEY ATIMETER SETTING AND INCREASE ALL MDA 140 FEET; INCREASE CIRCLING CATS A AND D VISIBILITY 1/4 MILE, AND INCREASE LNAV CATS C AND D AND CIRCLING CAT C VISIBILITY 1/2 MILE.  
CHART NOTE: DME/DME RNP-0.3 NA.  
(SEE FORM 8260-10)

QUALITY  
Checked

CITY AND STATE WILLIAMSON, WV	ELEVATION: 1882 THRE: 1826 AIRPORT NAME: APPALACHIAN RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS), RWY 8, ORIG-A 26 JULY 2012	SUP: AMDT: ORIG DATED 02/09/2012
----------------------------------	---	------------------------------	---	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

TAA

	FROM	TO	ALT
1.	347/30 CW 167/30 (NOPT)	SEPBU (IF/IAF) (FB)	5000
2.	167/30 CW 257/30	RUJAP (IAF) (FB)	5000
3.	257/30 CW 347/30	TAULS (IAF) (FB)	5400



CITY AND STATE WILLIAMSON, WV	ELEVATION: 1882      THRE: 1826	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, ORIG-A 26 JULY 2012	SUP:
	AIRPORT NAME: APPALACHIAN RGNL			AMDT:      ORIG
				DATED:      02/09/2012



**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	RUJAP	RUJAP	010	IAP	IF		FB					
	RUJAP	SEPBU	020		TF		FB	1.0	166.9(159.9T)	005.0	AA 05000	
	SEPBU	SEPBU	010	IAP	HF	R	FO		076.9(069.9T)	005.0	AA 05000	
	TAULS	TAULS	010	IAP	IF		FB					
	TAULS	SEPBU	020		TF		FB	1.0	346.9(339.9T)	005.0	AA 05000	
		SEPBU	010	FACF	IF		FB				AA 05000	
		UBIRE	020	PAF	TF		FB	0.5	076.9(069.9T)	006.5	AA 03800	
		RW08	030	MAP	TF		FO	0.3	077.0(070.0T)	006.0	AT 01866	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		077.0(070.0T)		AA 02282	
	NEGVE	050		DF		FO				AA 05000	
	NEGVE	060		HM	R	FO		257.2(250.2T)	005.0	AA 05000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	NEGVE	N374518.18	W0815201.30	N3745.303	W08152.022
	RUJAP	N374110.54	W0822445.78	N3741.176	W08224.763
	SEPBU	N373628.54	W0822235.77	N3736.476	W08222.596
	TAULS	N373146.49	W0822026.04	N3731.775	W08220.434
	UBIRE	N373843.17	W0821452.75	N3738.720	W08214.879
	RW08	N374045.91	W0820748.67	N3740.765	W08207.811

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW08	01826	40



CITY AND STATE <b>WILLIAMSON, WV</b>	ELEVATION: <b>1882</b> THRE: <b>1826</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: <b>APPALACHIAN RGNL</b>		<b>RNAV (GPS) RWY 8, ORIG-A</b>	AMDT: <b>ORIG</b>
			<b>26 JULY 2012</b>	DATED: <b>02/09/2012</b>