

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SIGNL	NICHE (TF) (FB) (RNP 2.00)	225.45 / 5.20	4000
NICHE (IAF)	AHORE (TF) (FB) (RNP 1.00)	192.74 / 5.94	3000
AHORE (IF)	COXOK (TF) (FB) (RNP 1.00)	139.68 / 6.10	1600
COXOK (FAF)	RW13 (MAP) (TF) (FO) (RNP 0.30)	139.74 / 4.79	
RW13 (MAP)	420 MSL (CA)	139.74	
420 MSL	SIGNL (DF) (FO) (RNP 1.00)		5000

LNAV: RW13

CLIMBING LEFT TURN TO 5000 DIRECT SIGNL AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000.

ADDITIONAL FLIGHT DATA:
HOLD NE, RT, 225.45 INBOUND.
CHART FAS OBST: 248 TOWER 264600N/0810455W.
CHART: IMMOKALEE RGNL AWOS-3
COXOK TO RW13: 3.04/35

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT AHORE
3. FAC: 139.74 FAF: COXOK DIST FAF TO MAP: 4.79 THLD: 4.79
4. MIN. ALT: AHORE 3000, COXOK 1600
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 20:1 IS CLEAR 34:1 IS CLEAR
8. MSA FROM: RW13 1700

MAG VAR: **5W** EPOCH YEAR: **2010**

MINIMUMS

TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>	ALTERNATE: N <input type="checkbox"/> A <input checked="" type="checkbox"/> X <input type="checkbox"/>														
CATEGORY <u>=====</u> >	A	B	C	D	E										
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	620	1	600	620	1	600	620	1 3/4	600	620	1 3/4	600			
CIRCLING	620	1	600	620	1	600	620	1 3/4	600	680	2	660			

NOTES:
CHART NOTE: USE IMMOKALEE ALTIMETER SETTING; WHEN NOT RECEIVED, USE OKEECHOBEE ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET AND CIRCLING VISIBILITY CAT D 1/4 SM.
CHART NOTE: CIRCLING RWY 31 NA AT NIGHT.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SIGNL ON V511 NORTHWEST BOUND.
PBN REQUIREMENTS NOTE: RNP APCH.



CITY AND STATE CLEWISTON, FL	ELEVATION: 20 TDZE: 20 AIRPORT NAME: AIRGLADES	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMD T NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG-A 24 MAY 2018	SUP: AMD T: ORIG DATED 03/12/2009
--	---	-------------------------------------	--	---