

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> W22	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 11	<u>ORIGINAL/AMENDMENT</u> 2E	<u>CITY</u> BUCKHANNON	<u>STATE</u> WV		
<u>AIRPORT ELEVATION</u> 1635	<u>TDZE</u> 1635	<u>SUPERSEDED</u> RNAV (GPS) RWY 11	<u>ORIGINAL/AMENDMENT</u> 2D	<u>DATED</u> 12/02/2021	<u>MAG VAR</u> 8W	<u>EPOCH YEAR</u> 2005
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 5 OCTOBER 2023	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
EKN VORTAC		HERIS		TF	FO	1.00	297.06	21.12	4000
CKB VOR/DME		HERIS		TF	FO	1.00	229.96	18.07	4000
ZOBIG	IAF	HERIS	NOPT	TF	FB	1.00	146.44	9.77	4000
HERIS	IF/IAF	HONVO		TF	FB	1.00	106.09	6.10	3400
HONVO	FAF	RW11	MAP	TF	FO	0.30	106.17	5.43	
RW11	MAP	2035 MSL		CA			106.17		
2035 MSL		HERIS		DF	FO	1.00			4000

MISSED APPROACH

MAP:

LP: RW11
 LNAV: RW11

MISSED APPROACH INSTRUCTIONS:

CLIMBING RIGHT TURN TO 4000 DIRECT HERIS AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



CHANGES - REASONS

1. ADDED CHART PROFILE NOTE "VISUAL SEGMENT - OBSTACLES" - IAW 8260.19I 8-6-10(O)(2)
2. REMOVED ADDITIONAL FLIGHT DATA PROCEDURE "HENVO TO RW11: 3.00/40" - PER FLIGHT INSPECTION
3. REMOVED CHART NOTE "CHART VDP AT 1.65 NM TO RW11" - PER FLIGHT INSPECTION
4. CRC REMAINDER CHANGED FROM "568A1437" TO "664AFCA3"
5. UPDATED ALTIMETER CONTINGENCY FROM "CIRCLING CAT B VISIBILITY 1/4 SM CAT. C VISIBILITY 3/4 SM" TO "CIRCLING CAT C VISIBILITY 1/2 SM" - UPDATED KCKB ALTIMETER MINIMUMS
6. CHANGED PBN REQUIREMENTS NOTE FROM "RNP APCH" TO "RNP APCH - GPS" - IAW 8260.19I 8-6-8 MEMO

COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☐ **OTHER:**

FLIGHT CHECKED BY

JORGE A MALCUN

Digitally signed by
JASON KRETSCHMER
Aug 04, 2023

OFFICE

FPO

DATE

08/04/2023

DEVELOPED BY

JASON KRETSCHMER (CHRISTOPHER MENDENHALL)

Digitally signed by
JASON KRETSCHMER
Jun 27, 2023

OFFICE

AJV-A421

DATE

06/20/2023

APPROVED BY

MARLON ROBINSON

Digitally signed by
JASON KRETSCHMER
Jun 27, 2023

OFFICE

AJV-A420

DATE

10/05/2023

TITLE

MANAGER

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	W22
RUNWAY	RW11
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W11A
LTP/FTP LATITUDE	390005.1155N
LTP/FTP LONGITUDE	0801656.1510W
LTP/FTP ELLIPSOIDAL HEIGHT	+04652
FPAP LATITUDE	385952.3200N
FPAP LONGITUDE	0801503.0400W
THRESHOLD CROSSING HEIGHT (TCH)	0.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	0.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1472
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	00.0
CRC REMAINDER	664AFCA3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+04973
FPAP ORTHOMETRIC HEIGHT	+04973

