

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Callings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
TAPDE WP	WOKAR WP (TF) (FB)	080.12/31.11	11000	LNAV: RW31
EMUXE WP	WOKAR WP (TF) (FB)	129.15/25.63	11000	
CARTY WP (IAF)	WOKAR WP (NOPT) (TF) (FB)	238.47/8.45	10000	CLIMB TO 11000 DIRECT ZUROS WP AND LEFT TURN VIA 301.61 TRACK TO EMUXE WP AND HOLD.
WOKAR WP (IF/IAF)	CINAN /3.00 NM TO EYEDI WP (TF) (FB)	312.19/3.00	9700	
CINAN	EYEDI WP (TF) (FB)	312.19/3.00	9000	ADDITIONAL FLIGHT DATA: HOLD W, LT, 091.78 INBOUND FAS OBST: 6849 TOWER 350840/1075341 CHART: 7120 TOWER 350412/1074651 EYEDI TO RW31 3.00/40 CHART VDP AT 1.71 NM TO RW31 CHART: ASOS CHART AIRPORT ELEV: 6537 CHART TDZE: 6522 FINAL SEGMENT: (TF)
RW31 (MAP)	6937 MSL (CA)	312.15		
6937 MSL	ZUROS WP (DF) (FB)			
ZUROS WP	EMUXE WP (TF) (FO)	301.61/7.05	11000	

- PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SE WOKAR WP, RT, 312.19 INBOUND, 10000 FT. IN LIEU OF PT (IAF)
- FAC: 312.15 FAF: EYEDI WP DIST FAF TO MAP: - THLD: 7.67
- MIN. ALT: WOKAR WP 10000, CINAN 9700, EYEDI WP 9000, YUDUN/2.53 NM TO RW31 7360
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS CLEAR
- MSA FROM: RW31 12600

MAG VAR: 12E EPOCH YEAR: 85

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A X												
CATEGORY ==>	A			B			C			D			E			
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	
LNAV MDA	7100	1	578	7100	1	578	7100	1 1/2	578			NA				
CIRCLING	7160	1	623	7160	1	623	7160	1 3/4	623			NA				

NOTES:
GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.
CIRCLING NOT AUTHORIZED EAST OF RWYS 13 - 31.

CITY AND STATE	ELEVATION: 6537 TDZE: 6522	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: JAN 20 2005	SUP: ORIG
GRANTS, NM	AIRPORT NAME: GRANTS-MILAN MUNI		RNAV (GPS) RWY 31, ORIG-A	DATE 02/19/2004

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM TO COURSE AND DISTANCE ALTITUDE

PROCEDURE NA FOR ARRIVALS AT EMUXE VIA V291 WESTBOUND.

CITY AND STATE GRANTS, NM	ELEVATION: 6537 TDZE: 6522 AIRPORT NAME: GRANTS-MILAN MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: JAN 20 2005 RNAV (GPS) RWY 31, ORIG-A	SUP:
				AMDT: ORIG
				DATED: 02/19/2004