FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE ILS STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.29

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT WILKES COU	ZAITA OTTI ID	<u>PROCEDURE NAME</u> ILS Z OR LOC Z RWY 1	<u>Original/amendme</u> Orig-a		<u>CITY</u> NORTH WILKESBORO		
AIRPORT ELEVATION 1303	<u>TDZE</u> 1276	<u>SUPERSEDED</u> ILS Z OR LOC Z RWY 1	ORIGINAL/AMENDMENT ORIG	DATED 08/17/2017	MAG VAR 8W	EPOCH YEAR 2020	
FACILITY	COORDINATES OF FACILITIES	ACTUAL EFFECTIVE DATE	REQUIRED EFFECTIVE DATE	CANCEL/SUS	PEND		

I-UKF

COORDINATES OF FACILITIES

REQUIRED EFFECTIVE DATE

16 JULY 2020

ROUTINE

TAA

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE	
1. 277/30 CW 097/30	NOPT	HAPRI	IF/IAF	5000	
2. 097/30 CW 277/30		097/15 CW 277/15		7100	
3. 097/15 CW 277/15		HAPRI	IF/IAF	5000	

TERMINAL ROUTES

<u></u>											
FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	<u>COURSE</u>	DISTANCE	ALTITUDE		
HAPRI/I-UKF 14.34 DME	IF/IAF	IRIVE/I-UKF 8.34 DME					006.65	6.00 (I-UKF)	3600		

MISSED APPROACH

MAP:

ILS: DA

LOC: I-UKF LOC 1.14 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1740 THEN CLIMBING RIGHT TURN TO 5000 HEADING 165 AND BZM VOR/DME R-050 DIRECT HAPRI/I-UKF 14.34 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



AIRPORT AIRPORT ID PROCEDURE NAME ORIGINAL/AMENDMENT CITY
WILKES COUNTY KUKF ILS Z OR LOC Z RWY 1 ORIG-A NORTH WILKESBORO

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. HOLD S HAPRI, RT, 006.65 INBOUND, 5000 FT. IN LIEU OF PT (IAF), MAX 5800.

3. FAC: 006.65 **FAF:** IRIVE/I-UKF 8.34 DME **DIST FAF TO MAP: DIST FAF TO THLD:** 7.20

4. MIN ALT: HAPRI/I-UKF 14.34 DME 5000, IRIVE/I-UKF 8.34 DME 3600, JATLO/I-UKF 3.84 DME 2160*

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: 1034

6. MIN GS INCPT: 3600 **GS ALT AT FAF**: IRIVE/I-UKF 8.34 DME 3600 **OM**: **MM**: **IM**:

7. GP ANGLE: 3.00 **34:1**: **20:1**: TCH: 59.4

8. MSA FROM:

EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED.

RNAV 1-GPS REQUIRED.

NOTES:

CHART NOTE: VDP NA WHEN USING HICKORY ALTIMETER SETTING:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HICKORY ALTIMETER SETTING AND INCREASE S-ILS DA TO 1569 FEET AND ALL MDAS 100 FEET, AND INCREASE S-LOC CATS C/D VISIBILITY 3/8 SM AND CIRCLING CAT C VISIBILITY 1/2 SM.

CHART NOTE: FOR INOPERATIVE ALS WHEN USING HICKORY ALTIMETER SETTING, INCREASE S-ILS ALL CATS VISIBILITY AND S-LOC CAT C/D VISIBILITY 3/8 SM.

ADDITIONAL FLIGHT DATA:

CHART FAS OBST: 1312 TREE 361210N/0810600W.

CHART VDP AT 2.12 DME*

DISTANCE VDP TO THLD 0.98 NM.

*LOC ONLY.

CHART CIRCLING ICON.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ILS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE.; LOC: STANDARD - CAT D 1000-3, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A		В		С		D			E					
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-ILS 01	1476	1/2	200	1476	1/2	200	1476	1/2	200	1476	1/2	200			
S-LOC 01	1640	1/2	364	1640	1/2	364	1640	5/8	364	1640	5/8	364			
CIRCLING	1800	1	497	1880	1	577	1880	1 1/2	577	2240	3	937			

CHANGES - REASONS

1. RADAR REMOVED FROM FIXES HAPRI, IRIVE AND JATLO - RADAR COVERAGE UNAVAILABLE.

2. INCREASED LOC MDA/HAT FROM 1620/344 TO 1640/364. - INCORPORATION OF FDC 9/5603 FOR NEW MISSED CONTROLLING OBSTACLE.

3. UPDATED WHEN LOCAL ALTIMETER SETTING NOT RECEIVED NOTE FROM INCREASE S-LOC CATS C/D VISIBILITY 1/4 SM TO 3/8 SM - INCORPORATION OF FDC 9/5603.

4. DELETED "CHART NOTE: DME OR RADAR REQUIRED" - NOTE CHANGED TO "DME REQUIRED" DUE TO INSUFFICIENT RADAR COVERAGE. NOTE MOVED TO EQUIPMENT REQUIREMENTS NOTES.

5. DELETED "CHART PLANVIEW NOTE: RNAV 1-GPS OR RADAR REQUIRED" FROM ADDITIONAL FLIGHT DATA - NOTE CHANGED TO "RNAV 1-GPS REQUIRED" DUE TO INSUFFICIENT RADAR COVERAGE. NOTE MOVED TO EQUIPMENT REQUIREMENTS NOTES.

6. DELETED DIST TO FAF TO MAP: 7.20 - DME REQUIRED. TIME/DISTANCE TABLE NOT NECESSARY.

OVALITY,

10

<u>STATE</u>

NC

COORDINATED WITH: AOPA X APA X NBAA X A4A ALPA X HAI 🗌 OTHER: ZTL, UKF AMGR **FLIGHT CHECKED BY OFFICE** DATE Digitally signed by PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020, SUBJECT: **WARDELL HENNING** FLIGHT INSPECTION REVIEW NOT REQUIRED Digitally signed by May 15, 2020 **DEVELOPED BY OFFICE** DATE **WARDELL HENNING** WARDELL HENNING (CASEY HILL) 01/30/2020 AJV-A432 May 15, 2020 Digitally signed by **TITLE** APPROVED BY **OFFICE** DATE **GEORGE DAVIS WARDELL HENNING** AJV-A430 MANAGER

PROCEDURE NAME

ILS Z OR LOC Z RWY 1

ORIGINAL/AMENDMENT

ORIG-A

<u>CITY</u>

NORTH WILKESBORO

STATE

NC

<u>AIRPORT</u>

WILKES COUNTY

May 15, 2020

AIRPORT ID

KUKF