

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**

TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KEHA	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 22	<u>ORIGINAL/AMENDMENT</u> 1C	<u>CITY</u> ELKHART	<u>STATE</u> KS		
<u>AIRPORT ELEVATION</u> 3622	<u>TDZE</u> 3615	<u>SUPERSEDED</u> RNAV (GPS) RWY 22	<u>ORIGINAL/AMENDMENT</u> 1B	<u>DATED</u> 11/07/2019	<u>MAG VAR</u> 7E	<u>EPOCH YEAR</u> 2010
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 7 OCTOBER 2021	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TAA

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE
1. 132/30 CW 312/30	NOPT	SUMTE	IF/IAF	5300
2. 312/30 CW 042/30		312/15 CW 042/15		6000
3. 312/15 CW 042/15		NANIC	IAF	5300
4. 042/30 CW 132/30		042/15 CW 132/15		6000
5. 042/15 CW 132/15		DENCA	IAF	5300

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
NANIC	IAF	SUMTE	NOPT	TF	FB	1.00	311.58	5.00	5300
DENCA	IAF	SUMTE	NOPT	TF	FB	1.00	131.50	5.00	5300
SUMTE	IF/IAF	HAKUK		TF	FB	1.00	221.54	6.10	5300
HAKUK	FAF	RW22	MAP	TF	FO	0.30	221.48	5.16	
RW22	MAP	4022 MSL		CA			221.48		
4022 MSL		RIGGO		DF	FO	1.00			6000



CHANGES - REASONS

1. ADDED "MAX 14000" TO PROFILE VIEW LINE 2 - IAW 8260.19I, 8-6-7,B,2.
2. MOVED BACKUP ALTIMETER NOTE - MOVED TO -9 AS A CONTINGENCY - IAW 19I 8-6-9, F, 3.
3. LNAV HAT CHANGED FROM 486 FT TO 485 FT - NEW SURVERY DATA
4. CHANGED PBN REQUIRMENTS NOTE FROM "RNP APCH" TO "RNP APCH - GPS" - IAW .19I 8-6-8, B(2)
5. REMOVED CHART VDP AT 1.47 NM TO RW22 - VDP NOT ESTABLISHED/20:1 SURFACE NOT CLEAR.
6. ADDED 20:1 IS NOT CLEAR TO LINE 7 AND CHANGED 34:1 FROM CLEAR TO NOT CLEAR IAW 19I, 8-6-7,G,3,A.
7. DELETED CHART NOTE CHART NOTE: VDP NA WHEN USING LIBERAL ALTIMETER SETTING - TO CLEAR NOTAM FDC 0/4889, VDP NOT PUBLISHED 20:1 SURFACE NOT CLEAR.
8. LNAV CAT C VISIBILITY CHANGED FROM 1 1/4 SM TO 1 3/8 SM - NEW VISIBILITY TABLES.

COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒ **OTHER:** ZKC, ICT FSS, ARPT MANAGER

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

Digitally signed by

DATE

JON DENTON

Mar 10, 2021

DEVELOPED BY

JON DENTON (JANTZEN TAYLOR)

Digitally signed by

JON DENTON

Mar 10, 2021

OFFICE

AJV-A432

DATE

12/11/2020

APPROVED BY

LONNIE EVERHART

Digitally signed by

JON DENTON

Mar 10, 2021

OFFICE

AJV-A430

DATE

TITLE
MANAGER

