

**Federal Aviation
Administration**

Transmittal Letter 22-01

November 12, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/30/2021	FL	Jacksonville	Jacksonville Exec At Craig	1/5141	8/16/2021	RNAV (GPS) RWY 32, Amdt 1A

AIRAC Date: 30 DECEMBER 2021

FDC 1/5141 CRG IAP JACKSONVILLE EXEC AT CRAIG, JACKSONVILLE, FL. RNAV (GPS) RWY 32, AMDT 1A... CIRCLING CAT B MDA 600/ HAA 559, CAT C MDA 620/HAA 579, CAT D MDA 800/HAA 759, VIS CAT D 2 1/2. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2; NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JACKSONVILLE INTL ALTIMETER SETTING: INCREASE LPV DA TO 273 FEET; INCREASE LNAV/VNAV DA TO 413 FEET; INCREASE ALL MDAS 40 FEET AND CIRCLING VISIBILITY CAT C 1/4 SM. THIS IS RNAV (GPS) RWY 32, AMDT 1B. 2107071207-PERM