

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
TICUR (IAF)	OYASA (NOPT) (FB)	081.26 / 5.00	3700
PACKI (IAF)	OYASA (NOPT) (FB)	261.58 / 5.00	3700
OYASA (IF/IAF)	VUPUY (FB)	171.42 / 3.00	2900
VUPUY	SEBEE (FB)	171.42 / 3.00	2400

LNAV: NOTIE

CLIMBING LEFT TURN TO 3700 DIRECT OYASA AND HOLD,
CONTINUE CLIMB-IN-HOLD TO 3700.

ADDITIONAL FLIGHT DATA:

CHART FAS OBST: 366 TREE 623910N/1601116W
SEBEE TO RW17: 3.06/35
756 AAO 624450N/1600818W

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD N OYASA, RT, 171.42 INBOUND, 3700 FT. IN LIEU OF PT (IAF)
- FAC: 171.40 FAF: SEBEE DIST FAF TO MAP: 5.92 THLD: 6.42
- MIN. ALT: OYASA 3700, VUPUY 2900, SEBEE 2400, PUCOY/2.10 NM TO NOTIE 1140
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
- GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR
- MSA FROM: _____

MAG VAR: 15E

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	700	1	412	700	1	412	700	1 1/4	412	700	1 1/4	412			
CIRCLING	740	1	431	760	1	451	760	1 1/2	451	860	2	551			

NOTES:
CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT.
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE ANVIK, AK	ELEVATION: 309 TDZE: 288 AIRPORT NAME: ANVIK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO.: RNAV (GPS) RWY 17, ORIG SEP 25 2008	SUP: AMDT: NONE DATED
-----------------------------	--	------------------------------	---	-----------------------------

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOLY CROSS ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT C 1/4 MILE, CAT D 1/2 MILE.

TAA

	FROM	TO	ALT
1.	081/30 CW 262/30 (NOPT)	081/15 CW 262/15	5100
2.	081/15 CW 262/15	OYASA (IF/IAF) (FB)	3700
3.	262/30 CW 351/30	262/18 CW 351/18	4200
4.	262/18 CW 351/18	PACKI (IAF) (FB)	3700
5.	351/30 CW 081/30	351/10 CW 081/10	4800
6.	351/10 CW 081/10	TICUR (IAF) (FB)	3700

CITY AND STATE

ANVIK, AK

ELEVATION: 309

TDZE: 288

AIRPORT NAME:

ANVIK

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 17, ORIG

SEP 25 2008

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

CITY AND STATE ANVIK, AK	ELEVATION: 309 TDZE: 288 AIRPORT NAME: ANVIK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO.: RNAV (GPS) RWY 17, ORIG SEP 25 2008	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	OYASA	OYASA	010		HF	R	FB		171.4 (186T)	004.0	03700
	PACKI	PACKI	010	IAF	IF		FB				
	PACKI	OYASA	020		TF		FB	1.0	261.6 (277T)	005.0	03700
	TICUR	TICUR	010	IAF	IF		FB				
	TICUR	OYASA	020		TF		FB	1.0	081.3 (096T)	005.0	03700
		OYASA	010	FACF	IF		FB				03700
		VUPUY	011	SDF	TF		FB	0.5	171.4 (186T)	003.0	02900
		SEBEE	020	FAF	TF		FB	0.5	171.4 (186T)	003.0	02400
		PUCOY	021	SDF	TF		FB	0.3	171.4 (186T)	003.8	01140
		NOTIE	030	MAP	TF		FO	0.3	171.4 (186T)	002.1	00477

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	171.4 (186T)		00700
	OYASA	050		DF	L	FO	1.0			03700
	OYASA	060		HM	R	FO	2.0	171.4 (186T)	004.0	03700

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	NOTIE	N623939.67	W1601112.25	N6239.661	W16011.204
	OYASA	N625128.26	W1600818.77	N6251.471	W16008.313
	PACKI	N625054.40	W1595728.40	N6250.907	W15957.473
	PUCOY	N624144.51	W1601041.86	N6241.742	W16010.698
	SEBEE	N624531.55	W1600946.39	N6245.526	W16009.773
	TICUR	N625201.29	W1601909.55	N6252.022	W16019.159
	VUPUY	N624829.93	W1600902.65	N6248.499	W16009.044
	RW17	N623909.95	W1601119.48	N6239.166	W16011.325

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW17	00283	35

CITY AND STATE
ANVIK, AK

ELEVATION: 309 TDZE: 288
 AIRPORT NAME:
 ANVIK

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:
 RNAV (GPS) RWY 17, ORIG
 SEP 25 2008

SUP:
 AMDT: NONE
 DATED: