

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
ORLANDO	SIX	ORLA6.ORLA	FIVE	09/08/2022	<b>23 Feb 2023</b>

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**DP ROUTE DESCRIPTION:**

TAKEOFF ALL RWYS: CLIMB ON ASSIGNED HEADING FOR RADAR VECTORS TO ASSIGNED ROUTE. MAINTAIN 7000. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.  
ALL AIRCRAFT: ATC CROSSING RESTRICTIONS AND CLIMB GRADIENTS: IF UNABLE TO ACCEPT CROSSING RESTRICTIONS AND CLIMB RATES ADVISE ATC PRIOR TO TAXI.  
RWY 35L/R, 36L/R: CROSS 2.0 DME SOUTH OF ORL VORTAC AT OR ABOVE 2300, CROSS ORL VORTAC R-115 AT OR ABOVE 2600, CROSS ORL VORTAC R-090 OR R-270 AT OR ABOVE 3000  
RWY 35L/R: 566 FT PER NM TO 3000, RWY 36L: 637 FT PER NM TO 3000, RWY 36R: 621 FT PER NM TO 3000.

**TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):**

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	---------------------------------	------------------------	----------------------	---------------	-----------------	------------	-------------	--------------------------------

**PROCEDURAL DATA NOTES:**

**PBN REQUIREMENTS NOTES:**

**EQUIPMENT REQUIREMENT NOTES:**

RADAR REQUIRED - TAKEOFF RWYS 35L, 35R, 36L, 36R: DME REQUIRED.

**TAKEOFF MINIMUMS:**

RWYS 17L, 17R, 18L 18R, 35L, 35R, 36L, 36R: STANDARD.

**TAKEOFF OBSTACLES NOTES:**

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

**CONTROLLING OBSTACLES:**

**MSA:**

**LOST COMMUNICATIONS PROCEDURES:**

**ADDITIONAL FLIGHT DATA:**

CHART: ORL VORTAC 2.0 DME, MINIMUM ALTITUDE 2300; ORL VORTAC R-115, MINIMUM ALTITUDE 2600; ORL VORTAC R-090 AND R-270, MINIMUM ALTITUDE 3000.  
CHART: TOP ALTITUDE: 7000.  
REFERENCE MAG VAR: KMCO 6W EPOCH YEAR: 2015.  
CHART: KORL.



<b>DP NAME</b> ORLANDO	<b>NUMBER</b> SIX	<b>DP COMPUTER CODE</b> ORLA6.ORLA	<b>SUPERSEDED NUMBER</b> FIVE	<b>DATED</b> 09/08/2022	<b>ACTUAL EFFECTIVE DATE</b> <b>23 Feb 2023</b>
---------------------------	----------------------	---------------------------------------	----------------------------------	----------------------------	--

**AIRPORTS SERVED:**

<b>AIRPORT ID</b>	<b>CITY</b>	<b>STATE</b>
KMCO	ORLANDO	FL

**COMMUNICATIONS:**

ATIS, CLNC DEL, GND CON, TOWER, CPDLC.

**FIXES AND/OR NAVAIDS:**

CRG VORTAC, SZW VORTAC, OMN VORTAC, OCF VORTAC, LAL VORTAC, PIE VORTAC, RSW VORTAC, PBI VORTAC, SRQ VOR/DME, MLB VOR/DME.

**REMARKS:**

1. THE ENVIRONMENTAL REVIEW UNDER FAA ORDER 1050.1F AND THE NOISE SCREENING HAVE BEEN ACCOMPLISHED.
2. LETTER OF APPROVAL ON FILE FOR THE PUBLICATION OF CLIMB GRADIENTS GREATER THAN 500 FT PER NM.
3. WAIVER ON FILE PERMITTING THE PUBLICATION OF ATC CLIMB GRADIENTS.
4. ABBREVIATED AMENDMENT.
5. NON-STANDARD EQUIPMENT REQUIREMENT NOTE DIRECTED BY AFS FROM PROCEDURES REVIEW BOARD (PRB).

**FLIGHT INSPECTED BY**

ROBERT E. WILLIAMS

*Digitally signed by*  
**MARK D ADAMS**  
Nov 10, 2022

**OFFICE**

FPO

**DATE**

09/17/2021

**DEVELOPED BY**

WILLIAM HANBY

*Digitally signed by*  
**WILLIAM HANBY**  
Sep 24, 2022

**OFFICE**

AJV-A412

**DATE**

08/24/2022

**APPROVED BY**

JULIE MORGAN

*Digitally signed by*  
**MARK D ADAMS**  
Nov 10, 2022

**OFFICE**

AJV-A410

**DATE**

**TITLE**

MANAGER

**REQUIRED EFFECTIVE DATE**

ROUTINE

**COORDINATED WITH:**

**A4A**  **ALPA**  **AOPA**  **APA**  **HAI**  **NBAA**  **OTHER:** ZJX, MCO APP CON, MCO ATCT, AMGR.

**CHANGES - REASONS:**

1. CHANGED EQUIPMENT REQUIREMENT NOTES FROM "RADAR REQUIRED." TO "RADAR REQUIRED - TAKEOFF RWYS 35L, 35R, 36L, 36R: DME REQUIRED." - PER FAO 8260.19I, PARA 8-3-4.C.(4) TO MITIGATE FDC 2/3653 MCO SID ORLANDO INTL, ORLANDO, FL. ORLANDO FIVE DEPARTURE ... CHANGE EQUIPMENT REQUIREMENT NOTES TO READ: RADAR REQUIRED - TAKEOFF RWYS 35L, 35R, 36L, 36R: DME REQUIRED. ALL OTHER DATA REMAINS AS PUBLISHED 2208241606-2304051604EST.
2. ADDED TO REMARKS: "4. ABBREVIATED AMENDMENT." - PER FAO 8260.46H, APPENDIX D, SECTION 2, PARA 17.C.
3. CHANGED DP ROUTE DESCRIPTION FROM "RWY 35L/R: 566 FT/NM TO 3000, RWY 36L: 637 FT/NM TO 3000, RWY 36R: 621 FT/NM TO 3000." TO "RWY 35L/R: 566 FT PER NM TO 3000, RWY 36L: 637 FT PER NM TO 3000, RWY 36R: 621 FT PER NM TO 3000." - PER FAO 8260.46H, PARA 2-1-1.E.(2).
4. REMOVED ORL VORTAC FROM FIXES AND/OR NAVAIDS - PER FAO 8260.46H, APPENDIX D, SECTION 2, PARA 15.
5. ADDED TO REMARKS: '5. NON-STANDARD EQUIPMENT REQUIREMENT NOTE DIRECTED BY AFS FROM PROCEDURES REVIEW BOARD (PRB).' - FOR HISTORICAL CONTINUITY.

