

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: OPNIC/13.80 DME FIX									
SHB VOR/DME (IAF)		LEEBR/8.00 DME			287.04 / 8.00			2600		CLIMBING LEFT TURN TO 2600 VIA SHB R-287 TO LEEBR/SHB 8.00 DME AND HOLD.									
LEEBR/8.00 DME (IF)		BOULD/11.00 DME			287.04 / 3.00 (SHB R-287)			2400											
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 287.04 INBOUND. FAS OBST: 1074 AAO 394138N/0860324W CHART 1068 POWER LINE 394100N/0860405W CHART 1020 TOWER 394259N/0860553W CHART 1028 HOSPITAL 394330N/0860602W CHART 1542 TOWER 394606N/0860144W INDIANAPOLIS DOWNTOWN HELIPORT, 732, 332.00/4.20									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 1E EPOCH YEAR: 1965									
2. PROFILE STARTS AT SHB VOR/DME																			
3. FAC 287.04 FAF BOULD/11.00 DME DIST FAF TO MAP _____ THLD _____																			
4. MIN. ALT SHB VOR/DME 2600, LEEBR 2600, BOULD 2400																			
8. MSA FROM: SHB VOR/DME 3100																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X									
CATEGORY =====>		COPTER																	
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
H-287	1340	3/4	1340																
NOTES:																			
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE INDIANAPOLIS INTERNATIONAL ALTIMETER SETTING AND INCREASE MDA 40 FEET.																			
CHART NOTE: ACTIVATE HIGH INTENSITY PAD LIGHTS - CTAF.																			
CHART PLANVIEW NOTE: CAUTION: HELIPORT LOCATED IN AREA OF NUMEROUS LIGHTED AND UNLIGHTED (CONTINUED ON PAGE 2)																			
CITY AND STATE		SURFACE ELEVATION: 732			FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP			24						
INDIANAPOLIS, IN		AIRPORT NAME:			SHB		COPTER VOR/DME 287, AMDT 2A			AMDT			2						
		INDIANAPOLIS DOWNTOWN					2 MARCH 2017			DATE			02/14/2008						

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):  
OBSTRUCTIONS.****CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON SHB VOR/DME AIRWAY RADIALS 231 CW 312.****CHART PLANVIEW NOTE: PROCEED VFR FROM OPNIC OR CONDUCT SPECIFIED MISSED APPROACH PROCEDURE.****SURFACE ELEVATION 824 FEET AT MAP.**

CITY AND STATE

INDIANAPOLIS, IN

**SURFACE ELEVATION: 732**

AIRPORT NAME:

INDIANAPOLIS DOWNTOWN

FACILITY  
IDENTIFIER:

SHB

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

**COPTER VOR/DME 287, AMDT 2A**

2 MARCH 2017

SUP:

AMDT:

DATED: 02/14/2008

QUALITY  
24  
CHECKED