FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE ILS STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT ID YNG	PROCEDURE NAME ILS OR LOC RWY 14		<u>ORIGI</u>	NAL/AMEND 9	<u>MENT</u>		<u>CITY</u> YOUNGSTOWN/W.	ARREN	STATE OH	
AIRPORT ELEVATION	TDZE SUPERSEDED			ORIGIN	AL/AME	NDMEN	IT DATED	MAG VAR E	POCH YEAR	
1192	1134	ILS OR LOC RWY 14			8D		03/26/2020	8W	1990	
FACILITY	COORDINATES OF FACILITIES		ACTUAL EFFECTIVE DATE REQUIRED			REQUI	RED EFFECTIVE DATE	CANCEL/SUSP	CANCEL/SUSPEND	
I-MQK			5 SEPTEMBER 2024 R				ROUTINE	ROUTINE		
TERMINAL ROUTES					1					
FROM	FIX TYPE	<u>T0</u>	FIX TYPE	LEG TYPE	FO/FB	<u>RNP</u>	COURSE	DISTANCE	ALTITUDE	
ACO VOR/DME		MOSKI OM/INT/ACO 23.66 DM	E				059.05	23.66	2900	
	16						142.05		2000	

OTNOE INT/RADAR	IF	MOSKI OM/INT					142.95	6.35 (I-MQK)	2900
MOSKI OM/INT	FAF	5.12 NM AFTER MOSKI OM/INT	MAP		FO		142.95	5.12	
5.12 NM AFTER MOSKI OM/INT	MAP	1334 MSL		CA			142.95		
1334 MSL		UNERE		DF	FO	1.00			2900

MISSED APPROACH

MAP:

ILS: DA LOC: 5.12 NM AFTER MOSKI OM/INT

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2900 DIRECT UNERE AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

	PT L	SIDE OF COUF	RSE 322.95	OUTBOUND	2900	FT WITHIN 1	0	MILES OF	MOSKI OM	/INT/ACO 23.66 E	OME (IAF)		
2.													
3.	FAC: 14	42.95	FAF: N	/IOSKI OM/INT		DIST FAF	ΓΟ ΜΑΡ:	5.12	DIST F	AF TO THLD:	5.12		
4.	MIN ALT:	MOSKI OM/INT 290	00										
5.	DIST TO	THLD FROM OM:	5.12 N	MM:	IM:	150 HAT:		GS ANT:	951				
6.	MIN GS II	NCPT: 2900	GS ALT AT PF	AF: GP INTCP				OM:	2794	MM:		IM:	
7.	GS ANGL	.E: 3.00	34:1:	2	0:1:	TCH:	57.2						
8.	MSA FRO	DM: FETCH LOM 09	90-270 3600, 270	0-090 3000									

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: CIRCLING RWY 5 AND 23 NA AT NIGHT.

ADDITIONAL FLIGHT DATA:

HOLD SE, RT, 323.09 INBOUND. CHART FAS OBST: 1193 TREE (39-131140) 411728N/0804259W. CHART CIRCLING ICON.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA

ILS: STANDARD; LOC: STANDARD

CATEGORY:		Α			В			С			D			Е	
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-ILS 14	1334	1/2	200	1334	1/2	200	1334	1/2	200	1334	1/2	200			
S-LOC 14	1580	1/2	446	1580	1/2	446	1580	7/8	446	1580	7/8	446			
CIRCLING	1640	1	448	1660	1	468	1740	1 1/2	548	1760	2	568			

CHANGES - REASONS

1. DECREASED LOC CAT C AND D VISIBILITY FROM 1 TO 7/8 SM. - 8260.3C TABLE 3-3-1.

2. REMOVED FEEDER FROM YNG VORTAC; ADDED FEEDER FROM ACO VOR/DME. - YNG VORTAC DECOMMISSIONING; ATC REQUEST.

3. ADDED STAND ALOND INTERMEDIATE SEGMENT FROM OTNOE. – ATC/FPT REQUEST.

4. TERMINAL ROUTES: ADDED MISSED APPROACH CA AND DF LEG. - RNAV MISSED APPROACH.

5. UPDATED LOC MAP: FROM "5.12 NM AFTER MOSKI OM/INT" TO "5.12 NM AFTER MOSKI OM/INT/ACO 23.66 DME." - MOSKI OM FIX DEFINITION UPDATED TO INCLUDE ACO DME.

6. UPDATED MISSED APPROACH INSTRUCTIONS FROM "CLIMB TO 1600 THEN CLIMBING RIGHT TURN TO 3600 ON HEADING 210 AND ON YNG VORTAC R-182 TO CAMES INT AND HOLD" TO "CLIMB TO 2900 DIRECT UNERE AND HOLD." – YNG VORTAC DECOMMISSIONING; FPT REQUEST.

7. REMOVED ALTERNATE MISSED APPROACH INSTRUCTIONS. – FPT REQUEST.

8. LINE 6: UPDATED GS INCPT AT OM FROM 2818 TO 2794. - NEW EVALUATION COMPLETED.

9. LINE 8: UPDATED MSA FROM YNG VORTAC 3600 TO FETCH LOM 090-270 3600, 270-090 3000. - YNG VORTAC DECOMMISSIONING; MATCH IL32 MSA.

10. ADDED PBN REQUIREMENTS NOTE: RNP APCH - GPS. - MISSED APPROACH TO WP UNERE HAS NO PRECISION COURSE GUIDANCE.

11. REMOVED CHART NOTE: RWY 14 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. - NO 34:1 PENETRATIONS FOUND.

12. REMOVED ADDITIONAL FLIGHT DATA: CHART AIRPORT ELV: 1192. – NO LONGER REQUIRED.

13. REMOVED ADDITIONAL FLIGHT DATA: CHART IN PLANVIEW: (LMCTG) 412417.76N/0805205.60W. - NO LONGER REQUIRED.

14. REMOVED ADDITIONAL FLIGHT DATA: CHART: ASR. - NO LONGER RÉQUIRED; NEED DETERMINED BY CHARTING.

15. REMOVED ADDITIONAL FLIGHT DATA: CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD SE FETCH LOM, RT, 322.97 INBOUND. – ALTERNATE MISSED REMOVED.

16. UPDATED ADDITIONAL FLIGHT DATA: FROM "1186 TOWER (39-003880) 411744N/0804341W" TO "1193 TREE (39-131140) 411728N/0804259W."

17. UPDATED CHART NOTE: FROM "CIRCLING RWY 5 NA AT NIGHT" TO "CIRCLING RWY 5 AND 23 NA AT NIGHT." - 20:1 PÉNETRATIONS FOUND ON RUNWAY 23.

18. ALTERNATE MINIMUMS: ADDED "ILS: STANDARD; LOC: STANDARD." - IAW 8260.19I 8-6-11B(4) AND MEMO.

AIRPORT ID YNG	PROCEDURE NAME ILS OR LOC RWY 14	ORIGINAL/AMENDMENT 9	<u>CITY</u> YOUNGSTOWN/WARREN	STATE OH
COORDINATED WITH:	<u>AOPA X APA HAI NBAA [</u>	X OTHER: ZOB, YNG APP CON, YNG ATCT, AMGR		
FLIGHT CHECKED BY		OFFICE	DATE	
SCOTT WIEBE	Digitally signed by	FPO	07/18/2024	
	JOSEPH L ZEDER			
<u>DEVELOPED BY</u> CASIMIR L. TABAKA (BARE	Jul 22, 2024 Digitally signed by BARA GORMAN) JOSEPH L ZEDER Jul 22, 2024	OFFICE AJV-A432	DATE 03/25/2024	
APPROVED BY CASIMIR L. TABAKA	Digitally signed by JOSEPH L ZEDER	OFFICE AJV-A430		<u>TITLE</u> ANAGER

Jul 22, 2024

