

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: MADTE/OVR 27.60 DME FIX
OVR VORTAC (IAF)	HUVNO/OVR 13.00 DME	141.68 / 13.00	2900	CLIMBING RIGHT TURN TO 2800 ON OVR VORTAC R-142 TO PICAM/OVR 23.00 DME AND HOLD.
HUVNO/OVR 13.00 DME (IF)	PICAM/OVR 23.00 DME	141.68 / 10.00 (OVR R-142)	2800	
				ADDITIONAL FLIGHT DATA: HOLD NW, RT, 141.68 INBOUND. FAS OBST: 1359 AAO 405023N/0952900W PICAM TO RW12: 3.05/55

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT HUVNO/OVR 13.00 DME
3. FAC 141.68 FAF PICAM/OVR 23.00 DME DIST FAF TO MAP THLD 5.54
4. MIN. ALT HUVNO 2900, PICAM 2800
8. MSA FROM: OVR VORTAC 3900 (30 NM)

MAG VAR: 8E

EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-12	1620	1 1/8	668	1620	1 1/8	668		NA			NA				
CIRCLING	1620	1 1/8	649	1620	1 1/4	649		NA			NA				

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: STRAIGHT-IN/CIRCLING RWY 12 PROCEDURE NA AT NIGHT.
 CHART NOTE: CIRCLING RWY 22 NA AT NIGHT.
 CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 30 NA AT NIGHT.
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
CHECKED

CITY AND STATE SHENANDOAH, IA	ELEVATION: 971 THRE: 952 AIRPORT NAME: SHENANDOAH MUNI	FACILITY IDENTIFIER: OVR	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 12, AMDT 4 SEPT 22, 2011	SUP VOR/DME OR GPS RWY 12
				AMDT 3A
				DATE 03/25/1999

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLARINDA ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON OVR VORTAC AIRWAY RADIALS 104 CW 192.

QUALITY
1
CHECKED

CITY AND STATE SHENANDOAH, IA	ELEVATION: 971 THRE: 952 AIRPORT NAME: SHENANDOAH MUNI	FACILITY IDENTIFIER: OVR	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: VOR/DME RWY 12, AMDT 4 SEPT 22, 2011	SUP: VOR/DME OR GPS RWY 12 AMDT: 3A DATED: 03/25/1999
----------------------------------	---	--------------------------------	---	--