

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
LOC STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.25**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT ID SNS	PROCEDURE NAME LOC RWY 31	ORIGINAL/AMENDMENT 6	CITY SALINAS	STATE CA
AIRPORT ELEVATION 84	TDZE 82	SUPERSEDED LOC RWY 31	ORIGINAL/AMENDMENT 5	DATED 05/19/2022
FACILITY I-SNS	COORDINATES OF FACILITIES	ACTUAL EFFECTIVE DATE 16 MAY 2024	REQUIRED EFFECTIVE DATE ROUTINE	MAG VAR 13E
				EPOCH YEAR 2020
				CANCEL/SUSPEND

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
SNS VORTAC		ARTYY/SNS 22.00 DME					107.00	22.00	5500
ARTYY/SNS 22.00 DME CW	IAF	AANNE/SNS 22.00 DME					22.00 DME ARC	(SNS LR-125)	5500
AANNE/SNS 22.00 DME	IF	FREZZ/SNS 17.06 DME					314.82	4.94 (I-SNS)	5400
FREZZ/SNS 17.06 DME		MRCDZ/SNS 15.06 DME					314.82	2.00 (I-SNS)	5300
MRCDZ/SNS 15.06 DME		CASTS/SNS 14.00 DME					314.82	1.06 (I-SNS)	4900
CASTS/SNS 14.00 DME		TATUM/SNS 10.25 DME					314.82	3.75 (I-SNS)	3800

MISSED APPROACH

MAP:

LOC: SNS 0.40 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 800 THEN CLIMBING LEFT TURN TO 3000 ON SNS VORTAC R-275 TO MARNA/SNS 10.92 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

- PT** **SIDE OF COURSE** **OUTBOUND** **FT WITHIN** **MILES OF** (IAF)
- PROFILE STARTS AT AANNE/SNS 22.00 DME
- FAC:** 314.82 **FAF:** TATUM/SNS 10.25 DME **DIST FAF TO MAP:** **DIST FAF TO THLD:** 9.87
- MIN ALT:** AANNE/SNS 22.00 DME 5500, FREZZ/SNS 17.06 DME 5400, MRCDZ/SNS 15.06 DME 5300, CASTS/SNS 14.00 DME 4900, TATUM/SNS 10.25 DME 3800, KNOLS/SNS 3.32 DME 1220
- MSA FROM:** SNS VORTAC 100-220 6300, 220-310 4200, 310-100 5200



EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED.

NOTES:

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON SNS VORTAC AIRWAY RADIALS 083 CW 167.
CHART NOTE: DME FROM SNS VORTAC. DME USE REQUIRES SIMULTANEOUS RECEPTION OF I-SNS AND SNS DME.
CHART NOTE: CIRCLING NA FOR CATS C AND D NE OF RWY 13 AND N OF RWY 26.
CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC-31 VISIBILITY CATS C AND D TO RVR 5000.

ADDITIONAL FLIGHT DATA:

HOLD W, RT, 095.00 INBOUND.
CHART FAS OBST: 119 POLE (06-162553) 363901N/1213530W.
295 AAO 363648N/1213321W.
CHART VDP AT 1.26 DME.
DISTANCE VDP TO THLD 0.87 NM.
TATUM TO RW31: 3.50/50.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA STANDARD - CAT D 1600-3, NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED.

CATEGORY:	A			B			C			D			E		
	FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS
S-LOC 31	420	2400	338	420	2400	338	420	4000	338	420	4000	338			
CIRCLING	540	1	456	540	1	456	800	2	716	1740	3	1656			

CHANGES - REASONS

1. PROFILE: CHANGED PROFILE STARTS AT FROM "AANNE" TO "AANNE/SNS 22.00 DME" - NEW SIAP FORMAT.
2. UPDATED MISSED APPROACH INSTRUCTIONS FROM "CLIMB TO 800 THEN CLIMBING LEFT TURN TO 4800 ON SNS VORTAC R-275 TO MARNA/SNS 10.92 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4800" TO "CLIMB TO 800 THEN CLIMBING LEFT TURN TO 3000 ON SNS VORTAC R-275 TO MARNA/SNS 10.92 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000" - ATC REQUEST FOR TRAFFIC DECONFLICTION AND NEW EVALUATION.
3. NOTES: RELOCATED "VDP NA WHEN USING MONTEREY ALTIMETER SETTING" TO 8260-9 PART C: GENERAL REMARKS AS CONTINGENCY NOTE - 8260.19I, 8-6-9 (E) (9).
4. ADDITIONAL FLIGHT DATA: DELETED 7:1 OBSTACLE "860 AAO 362945N/1213103W" - NEW TARGETS EVALUATION WITH 3DEP SOFTWARE.
5. ADDITIONAL FLIGHT DATA: DELETED "CHART SNS R-107 AT ARTYY" - REDUNDANT INFORMATION, SINCE THERE'S ALREADY A FEEDER FROM SNS TO ARTYY
6. MINIMUMS: UPDATED CAT C CIRCLING MDA/HAA FROM "780/696" TO "800/716" - TO CLEAR ACTIVE NOTAM FDC 3/1096.
7. MINIMUMS: INCREASED CAT D CIRCLING MDA/HAA FROM 1680/1596 TO 1740/1656 - NEW TARGETS EVALUATION WITH 3DEP SOFTWARE.



AIRPORT ID
SNS

PROCEDURE NAME
LOC RWY 31

ORIGINAL/AMENDMENT
6

CITY
SALINAS

STATE
CA

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA OTHER: ZOA, NORCAL APCH, SNS ATCT, AMGR

FLIGHT CHECKED BY

JOSEPH R JAQUISH

Digitally signed by

ERIC N SUSKI

Mar 15, 2024

OFFICE

FPO

DATE

03/06/2024

DEVELOPED BY

PARNELL PRASSADA

Digitally signed by

PARNELL R PRASSADA

Dec 21, 2023

OFFICE

AJV-A431

DATE

11/22/2023

APPROVED BY

ERIC N SUSKI

Digitally signed by

ERIC N SUSKI

Mar 15, 2024

OFFICE

AJV-A431

DATE

TITLE
MANAGER

