

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES										MISSED APPROACH										
FROM		TO			COURSE AND DISTANCE				ALTITUDE		MAP: 4.31 MILES AFTER TVC VOR/DME OR AT MAJRA/ 4.31 DME FIX CLIMB TO 1800 THEN CLIMBING RIGHT TURN TO 3000 DIRECT TVC VOR/DME AND HOLD.									
											ADDITIONAL FLIGHT DATA: HOLD S, RT, 340.00 INBOUND. CHART FAS OBST: 1009 TREE 444136N/0853447W FAC CROSSES MIDPOINT OF RWY 10-28 CHART CIRCLING ICON									
1. PT <u> L </u> SIDE OF COURSE <u> 164.87 </u> OUTBOUND <u> 3000 </u> FT WITHIN <u> 10 </u> MILES OF <u> TVC VOR/DME </u> (IAF)															MAG VAR: 2W EPOCH YEAR: 1965					
2.																				
3. FAC <u> 344.87 </u> FAF <u> TVC VOR/DME </u> DIST FAF TO MAP <u> 4.31 </u> THLD <u> </u>																				
4. MIN. ALT <u> TVC VOR/DME 2200, WAMOM/2.31 DME 1440* </u>																				
8. MSA FROM: <u> TVC VOR/DME 3600 </u>																				
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		@								
CATEGORY =====>		A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
CIRCLING	1440	1 1/4	816	1440	1 1/4	816	1500	2 1/2	876	1720	3	1096								
WAMOM FIX MINIMUMS (DME REQUIRED)																				
CIRCLING	1300	1	676	1300	1	676	1500	2 1/2	876	1720	3	1096								
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BELLAIRE ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND ALL CAT C VISIBILITY 1/4 MILE. CHART NOTE: CIRCLING TO RWY 18 NA AT NIGHT. CHART PROFILE NOTE: *1500 WHEN USING BELLAIRE ALTIMETER SETTING.																				
CITY AND STATE TRAVERSE CITY, MI		ELEVATION: 624 TDZE: AIRPORT NAME: CHERRY CAPITAL		FACILITY IDENTIFIER: TVC		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR-A, AMDT 21 12 DECEMBER 2013				SUP VOR OR TACAN OR GPS-A AMDT 20A DATE 09/28/2006										

 QUALITY
2
CHECKED