

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**

**TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> AMELIA EARHART	<u>AIRPORT ID</u> K59	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 16	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> ATCHISON	<u>STATE</u> KS	
<u>AIRPORT ELEVATION</u> 1073	<u>TDZE</u> 1073	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 2E	<u>EPOCH YEAR</u> 2020
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 26 MARCH 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

**TAA**

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE
1. 081/30 CW 261/30	NOPT	JETGI	IF/IAF	3000
2. 261/30 CW 351/30		WOMUR	IAF	3000
3. 351/30 CW 081/30		UZZOV	IAF	3000

**TERMINAL ROUTES**

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
WOMUR	IAF	JETGI		TF	FB	1.00	261.59	9.00	3000
UZZOV	IAF	JETGI		TF	FB	1.00	081.34	9.00	3000
JETGI	IF/IAF	WUXET		TF	FB	1.00	171.46	5.00	2700
WUXET	PFAF	RW16	MAP	TF	FO	0.30	171.47	5.06	
RW16	MAP	1500 MSL		CA			171.47		1500
1500 MSL		JETGI		DF	FO	1.00			3000

**MISSED APPROACH**

**MAP:**

LNAV: RW16

**MISSED APPROACH INSTRUCTIONS:**

CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3000 DIRECT JETGI AND HOLD.

**ALTERNATE MISSED APPROACH INSTRUCTIONS:**

QUALITY  
10  
CHECKED

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD N JETGI, RT, 171.46 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 171.47FAF: WUXETDIST FAF TO MAP: 5.06DIST FAF TO THLD: 5.06

4. MIN ALT: JETGI 3000, WUXET 2700

5. DIST TO THLD FROM OM:MM:IM:150 HAT:GS ANT:OM:MM:IM:

6. MIN GP INCPT:GP ALT AT FAF :

7. GP ANGLE:34:1: IS NOT CLEAR20:1: IS NOT CLEARTCH:

8. MSA FROM:

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.  
CHART NOTE: RWY 16 HELICOPTER VISIBILITY REDUCTION BELOW 1 NOT AUTHORIZED.

ADDITIONAL FLIGHT DATA:

WUXET TO RW16: 3.00/35.  
CHART CIRCLING ICON.  
FAS OBST: 1339 AAO 393642N/0951154W.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	1600	1	527	1600	1	527		NA			NA				
CIRCLING	1600	1	527	1620	1	547		NA			NA				

CHANGES - REASONS



COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZKC, STJ APP CON, MCI APP CON, APT MGR

FLIGHT CHECKED BY

SUSANNA ROBERTS

*Digitally signed by*

**ALLAN WILL**

Jan 07, 2020

OFFICE

FICO

DATE

1/2/20

DEVELOPED BY

TOMMY BYRNS

*Digitally signed by*

**TOMMY BYRNS**

Dec 20, 2019

OFFICE

AJV-A423

DATE

11/05/2019

APPROVED BY

MARLON ROBINSON

*Digitally signed by*

**ALLAN WILL**

Jan 07, 2020

OFFICE

AJV-A420

DATE

TITLE  
MANAGER

