

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
TACAN STANDARD INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.23**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> WAL	<u>PROCEDURE NAME</u> TACAN RWY 10	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> WALLOPS ISLAND	<u>STATE</u> VA
<u>AIRPORT ELEVATION</u> 40	<u>TDZE</u> 38	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u> 12W
<u>FACILITY</u> SBY	<u>COORDINATES OF FACILITIES</u> 382042.02N/0753038.07W	<u>ACTUAL EFFECTIVE DATE</u> 27 NOVEMBER 2025	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>MAG VAR</u> 12W
				<u>EPOCH YEAR</u> 2000
				<u>CANCEL/SUSPEND</u>

**TERMINAL ROUTES**

THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 25-24.

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
MAGGO/SBY 24.13 DME CCW	IF/IAF	ZUKPU/SBY 24.13 DME CCW					24.13 DME ARC	7.16	1700

**MISSED APPROACH**

**MAP:**


SBY R-189/24.13 DME

**MISSED APPROACH INSTRUCTIONS:**

CLIMBING LEFT TURN TO 2000 ON HEADING 240 AND SBY TACAN 24.13 DME ARC CLOCKWISE TO MAGGO/SBY 24.13 DME AND HOLD.

**ALTERNATE MISSED APPROACH INSTRUCTIONS:**

**PROFILE:**

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT MAGGO/SBY 24.13 DME CCW
- FAC: FAF: ZUKPU/SBY 24.13 DME CCW DIST FAF TO MAP:  DIST FAF TO THLD: 5.00
- MIN ALT: MAGGO/SBY 24.13 DME CCW 2000, ZUKPU/SBY 24.13 DME CCW 1700
- MSA FROM: SBY TACAN 270-360 2100, 360-270 1700 (26NM)

**NOTES:**

CHART PROFILE NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT (VGS1 ANGLE {ANGLE}/TCH {FEET}).  
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SBY ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE S-10 CAT A VISIBILITY 1/4 SM, AND CIRCLING CATS C AND D VISIBILITY 1/4 SM.  
 CHART NOTE: PROCEDURE NA WHEN R-6604 ACTIVE.

**ADDITIONAL FLIGHT DATA:**

CHART R-6604 A/B/C/D/E.  
 CHART SBY R-218 AT MAGGO.  
 CHART SBY R-201 AT ZUKPU.  
 ZUKPU TO RW10: 3.00/50.0.  
 HOLD SW, RT, 038.01 INBOUND.  
 CHART FAS OBST: 315 TOWER (51-001697) 375624N/0753231W.



**MINIMUMS:**

**TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT**

**ALTERNATE:** NA  CAT A, B 900-2, CAT C 900-2 1/2, CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E			
	FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-10	900	1 1/4	862	900	1 1/4	862	900	2 1/2	862	900	2 1/2	862				
CIRCLING	900	1 1/4	860	900	1 1/4	860	900	2 1/2	860	900	2 3/4	860				

**CHANGES - REASONS**

ORIGINAL PROCEDURE.

09/26/2025: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 09/12/2025.  
PROFILE VIEW: DELETED DIST FAF TO MAP.

**COORDINATED WITH:**

**A4A**  **ALPA**  **AOPA**  **APA**  **HAI**  **NBAA**  **OTHER:** ZDC, NHK APP CON, WAL ATCT, AMGR.

**FLIGHT CHECKED BY**

JON D HOLLAND

*Digitally signed by*

**CASIMIR L TABAKA**

Sep 12, 2025

**OFFICE**

AJF

**DATE**

09/10/2025

**DEVELOPED BY**

CASIMIR L. TABAKA (RONALD K. STROBACH)

*Digitally signed by*

**CASIMIR L TABAKA**

Sep 12, 2025

**OFFICE**

AJV-A432

**DATE**

01/29/2025

**APPROVED BY**

CASIMIR L. TABAKA

*Digitally signed by*

**CASIMIR L TABAKA**

Sep 12, 2025

**OFFICE**

AJV-A432

**DATE**

**TITLE**  
MANAGER

