

PAGE 1 OF 4 PAGES

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CAT C 1/4 MILE.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART NOTE: FOR INOPERATIVE MALSR WHEN USING TAMPA INTL ALTIMETER SETTING, INCREASE S-ILS 23 CATS

A/B/C VISIBILITY TO 7/8 MILE; INCREASE S-LOC 23 CATS A/B VISIBILITY TO 1 MILE.

CHART NOTE: VDP NA WHEN USING TAMPA INTL ALTIMETER SETTING.

QUALITY
6
CHECKED

CITY AND STATE
TAMPA, FL

ELEVATION: 22 THRE: 21
AIRPORT NAME:
TAMPA EXECUTIVE

FACILITY
IDENTIFIER:
I-VDF

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
ILS OR LOC RWY 23, AMDT 1
13 JAN 2011

SUP:
AMDT: ORIG
DATED: 06/08/2006

FLIGHT STANDARDS SERVICES - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KVDFK7FI23	I	010JUVASK7EA0E	D	IF	IVDFK7	04640156	PI	J	018000180018000		0	NS
SUSAP	KVDFK7FI23	I	020ERKEYK7EA0E	F	CF	IVDFK7	0464006122600095PI	H	0180001800	-310LAL	K7D	0	NS
SUSAP	KVDFK7FI23	I	030RW23 K7PG0GY	M	CF	IVDFK7	0464000822600053PI		00061	-310		0	NS
SUSAP	KVDFK7FI23	I	040	0 M	CA		2264		+ 00800			0	NS
SUSAP	KVDFK7FI23	I	050LAL	K7D 0VY	L	DF			+ 02000			0	NS
SUSAP	KVDFK7FI23	I	060LAL	K7D 0VE	L	HM	2751T010		+ 02000			0	NS

[illegible][illegible][illegible]

QUALITY
CHECKED

SUP:	
AMDT:	ORIG
DATED:	06/08/2006

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

ILS STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - ILS

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		JUVAS	010	FACF	IF		FB				AA 01800 GI 01800	
		ERKEY	020	FAF	CF		FB		226.0 ()	009.5	GI 01800 GS 01800	
		RW23	030	MAP	CF		FO		226.0 ()	005.3	AT 00061	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		226.4 ()		AA 00800	
	LAL	050		DF	L	FO				AA 02000	
	LAL	060		HM	L	FO		275.1 ()	T01.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	LAL	N275910.25	W0820049.99	N2759.171	W08200.833
	IVDF (DME)	N280037.44	W0822054.20	N2800.624	W08220.903
	ERKEY	N280508.98	W0821618.39	N2805.150	W08216.307
	JUVAS	N281210.58	W0820903.02	N2812.176	W08209.050
	RW23	N280114.34	W0822020.13	N2801.239	W08220.336
	IVDF (LOC)	N280039.96	W0822055.51	N2800.666	W08220.925

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW23	00021	40

QUALITY
CHECKED

CITY AND STATE
TAMPA, FL

ELEVATION: 22 THRE: 21
AIRPORT NAME:
TAMPA EXECUTIVE

FACILITY
IDENTIFIER:
I-VDF

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
ILS OR LOC RWY 23, AMDT 1
13 JAN 2011

SUP:
AMDT: ORIG
DATED: 06/08/2006