

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> GVT	<u>PROCEDURE NAME</u> RNAV (RNP) Z RWY 17	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> GREENVILLE	<u>STATE</u> TX
<u>AIRPORT ELEVATION</u> 535	<u>TDZE</u> 534	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>EPOCH YEAR</u> 1995
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 3 SEPTEMBER 2026	<u>MAG VAR</u> 5E	<u>CANCEL/SUSPEND</u>
		<u>REQUIRED EFFECTIVE DATE</u> ROUTINE		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
CABUN	IAF	JAYXX		TF	FB	1.00	298.14	14.55	4000
COBUG	IAF	UCECE		TF	FB	1.00	261.52	11.86	4000
KIDDD	IAF	JDAMM		TF	FB	1.00	228.42	23.22	4000
KLECH	IF	EKBLD		TF	FB	1.00	355.73	5.76	4000
EKBLD		POCNI		RF	FB	1.00	(3.50 NM RADIUS CCW (CFPMM))	10.98	2200
CIPEX	IF	POCNI		TF	FB	1.00	175.73	6.93	2200
JDAMM	IF	POCNI		TF	FB	1.00	175.74	5.66	2200
JAYXX	IF	ADODD		TF	FB	1.00	324.53	9.46	4000
ADODD		POCNI		RF	FB	1.00	(3.50 NM RADIUS CCW (CFRPM))	9.08	2200
UCECE	IF	WHIIP		TF	FB	1.00	261.60	3.84	4000
WHIIP		POCNI		RF	FB	1.00	(6.67 NM RADIUS CCW (CFMFP))	9.98	2200
POCNI	PFAF	RW17	MAP	TF	FO	0.30	175.73	5.10	
RW17	MAP	VECUN		TF	FO	1.00	175.73	13.33	3000

MISSED APPROACH

MAP:

RNP: DA

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 ON TRACK 175.73 TO VECUN AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

QUALITY
21
CHECKED

PROFILE:

1.	PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)									
2.	PROFILE STARTS AT POCNI														
3.	FAC:	175.73	FAF:	POCNI	DIST FAF TO MAP:	DIST FAF TO THLD:									
4.	MIN ALT:	POCNI 2200													
5.	DIST TO THLD FROM PFAF:	5.10	MM:	IM:	150 HAT:	305 HAT:	0.82	GS ANT:							
6.	MIN GP INCPT:	2200	GP ALT AT PFAF:	POCNI 2200		OM:		MM:		IM:					
7.	GP ANGLE:	3.00	34:1:	IS CLEAR	20:1:	IS CLEAR	TCH:	56.9							
8.	MSA FROM:	RW17 2400													

PBN REQUIREMENTS NOTE:

RNP AR APCH - GPS. AUTHORIZATION REQUIRED. FROM ADODD, EKBLD, WHIIP: RF.

NOTES:

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -16°C OR ABOVE 54°C.
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA.
CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO RNP 0.15. FOR INOPERATIVE ALS, INCREASE RNP 0.30 VISIBILITY ALL CATS TO 1 1/8 SM.

ADDITIONAL FLIGHT DATA:

HOLD S, RT, 355.73 INBOUND.
CHART AT OR BELOW 12000 AND AT OR ABOVE 4000 AT CABUN.
CHART AT OR BELOW 10000 AND AT OR ABOVE 4000 AT COBUG.
CHART AT OR BELOW 11000 AND AT OR ABOVE 4000 AT KIDDD.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD; NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
AUTHORIZATION REQUIRED															
RNP 0.15 DA	839	1	305	839	1	305	839	1	305	839	1	305			
RNP 0.30 DA	938	1	404	938	1	404	938	1	404	938	1	404			

CHANGES - REASONS



COORDINATED WITH:

A4A☐

ALPA☒

AOPA☒

APA☐

HAI☐

NBAA☒

OTHER: ZFW, GVT ATCT, AMGR

FLIGHT CHECKED BY

WILLIAM R GEISER

Digitally signed by

RAKE MCGRAW

Jun 29, 2026

OFFICE

AJF

DATE

06/26/2026

Digitally signed by

RAKE MCGRAW

Jun 29, 2026

OFFICE

AJV-A422

DATE

03/09/2026

APPROVED BY

RAKE MCGRAW

Digitally signed by

RAKE MCGRAW

Jun 29, 2026

OFFICE

AJV-A422

DATE

TITLE

MANAGER

