

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: VEYUG CLIMB TO 3000 DIRECT VAGYU AND RIGHT TURN VIA 011.87 TRACK TO HAWKN AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 183.55 INBOUND. CHART FAS OBST: 1238 ROD ON STROBE LTD TWR 430130N/0881124W CHART 1242 TOWER 430157N/0880907W. WERBI TO RW28: 3.38/37 FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD.								
BAE VORTAC	WIGBA (FB)	080.78 / 14.38	3000									
WIGBA (IAF)	WIDNO (FB)	180.07 / 7.00	3000									
WIDNO (IF)	WERBI (FB)	270.07 / 6.10	3000									
1. PT <u>NA</u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT WIDNO 3. FAC: <u>269.97</u> FAF: <u>WERBI</u> DIST FAF TO MAP: <u>5.25</u> THLD: <u>5.73</u> 4. MIN. ALT: <u>WIDNO 3000, WERBI 3000, VOVVU/1.50 NM TO VEYUG 1640</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1 IS NOT CLEAR</u> 8. MSA FROM: <u>VEYUG 2900</u>				MAG VAR: <u>1W</u> EPOCH YEAR: <u>1990</u>								
MINIMUMS												
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @							
CATEGORY =====>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1420	1	514	1420	1	514	1420	1 1/2	514	1420	1 3/4	514
CIRCLING	1460	1	549	1480	1	569	1520	1 3/4	609	1600	2 1/4	689
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LAWRENCE J TIMMERMAN ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE CIRCLING CAT C AND D VISIBILITY 1/4 MILE. SFE 8260-10												
CITY AND STATE		ELEVATION: 911 TDZE: 906		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
WAUKESHA, WI		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 28, ORIG			AMDT: NONE			
		WAUKESHA COUNTY				07 MAY 2009			DATED			

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON BAE VORTAC AIRWAY RADIALS 085 CW 119.

CITY AND STATE

WAUKESHA, WI

ELEVATION: 911 TDZE: 906

AIRPORT NAME:

WAUKESHA COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 28, ORIG

07 MAY 2009

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	BAE	BAE	010		IF		FB				
	BAE	WIGBA	020	IAF	TF		FB	2.0	080.8 (080T)	014.4	03000
	BAE	WIDNO	030		TF		FB	1.0	180.1 (179T)	007.0	03000
		WIDNO	010	FACF	IF		FB				03000
		WERBI	020	FAF	TF		FB	0.5	270.1 (269T)	006.1	03000
		VOVVU	021	SDF	TF		FB	0.3	270.0 (269T)	004.0	0164001662
		VEYUG	030	MAP	TF		FO	0.3	269.9 (269T)	001.3	01120

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	VAGYU	040		DF		FB	1.0			
	HAWKN	050		TF	R	FO	1.0	011.9 (011T)		03000
	HAWKN	060		HM	R	FO	2.0	183.6 (183T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BAE	N430700.67	W0881703.65	N4307.011	W08817.061
	HAWKN	N431800.15	W0881623.44	N4318.003	W08816.391
	VAGYU	N430213.44	W0882032.30	N4302.224	W08820.538
	VEYUG	N430220.08	W0881302.41	N4302.335	W08813.040
	VOVVU	N430221.81	W0881059.71	N4302.364	W08810.995
	WERBI	N430225.96	W0880553.11	N4302.433	W08805.885
	WIDNO	N430232.23	W0875733.91	N4302.537	W08757.565
	WIGBA	N430932.27	W0875743.22	N4309.538	W08757.720
	RW28	N430226.23	W0881341.93	N4302.437	W08813.699

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW28	00906	37

CITY AND STATE
WAUKESHA, WI

ELEVATION: 911 TDZE: 906
 AIRPORT NAME:
WAUKESHA COUNTY

FACILITY
 IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 28, ORIG
07 MAY 2009

SUP:
 AMDT: **NONE**
 DATED: