

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
SIE VORTAC	JENGA (FB)	068.96 / 21.14	2000	LPV: DA LNAV/VNAV: DA LNAV: RW31			
PANZE	RODDI (FB)	212.97 / 14.50	2000				
RODDI (IAF)	STEVV (FB)	218.18 / 6.00	2000	CLIMB TO 2000 DIRECT WEREK AND ON TRACK 258.79 TO KOVEC AND HOLD.			
JENGA (IAF)	STEVV (FB)	038.10 / 6.00	2000				
STEVV (IF)	PRSTY (FB)	308.14 / 6.10	1700	ADDITIONAL FLIGHT DATA: HOLD SW, RT, 037.82 INBOUND. CHART FAS OBST: 171 ROD 392718N/0743311W CHART FAS OBST: 178 ANTENNA TWR 392557N/0743027W CHART R-5002. CHART W-107. DISTANCE TO THLD FROM 200 HAT: 0.46 NM. CHART VDP AT 0.97 MILES TO RW31* LNAV ONLY. WAAS CHANNEL # 50113 REFERENCE PATH ID: W31A CHART ASR			

1. PT <u>NA</u> SIDE OF COURSE		OUTBOUND	FT WITHIN	MILES OF	(IAF)
2. PROFILE STARTS AT STEVV					
3. FAC: <u>308.07</u> FAF: <u>PRSTY</u>		DIST FAF TO MAP: <u>4.91</u>		THLD: <u>4.91</u>	
4. MIN. ALT: <u>STEVV 2000, PRSTY 1700, YIBKU/2.80 NM TO RW31 1000*</u>					
5. DIST TO THLD FROM OM: <u>MM:</u>		IM: <u>150</u>	HAT: <u>100</u>	GS ANT: <u></u>	
6. MIN GS INCPT: <u>1700</u>		GS ALT AT: <u>PRSTY 1700</u>	OM: <u></u>	MM: <u></u>	IM: <u></u>
7. GS ANGLE: <u>3.00</u>		TCH: <u>52.4</u> 34:1 IS CLEAR			
8. MSA FROM: <u>RW31 2100</u>					

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	263	4000	200	263	4000	200	263	4000	200	263	4000	200	263	4000	200
LNAV/VNAV DA	421	6000	358	421	6000	358	421	6000	358	421	6000	358	421	6000	358
LNAV MDA	440	5000	377	440	5000	377	440	5000	377	440	6000	377	440	6000	377
CIRCLING	540	1	465	540	1	465	540	1 1/2	465	640	2	565	760	2 1/2	685

NOTES:

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F).

CHART NOTE: DME/DME RNP-0.3 NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT PANZE VIA V44, V184-229 NORTHEAST BOUND AND FOR ARRIVALS AT SIE VORTAC ON AIRWAY RADIALS 333 CW 059.

SEE 8260-10

@ CAT E 800-2 1/2

CITY AND STATE	ELEVATION: 75 TDZE: 63	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 31, AMDT 3 23 SEP 2010	SUP: RNAV (GPS) RWY 31
ATLANTIC CITY, NJ	AIRPORT NAME: ATLANTIC CITY INTL			AMDT: 2
				DATED 09/25/2008

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

***LNAV ONLY**

QUALITY
CHECKED

CITY AND STATE

ATLANTIC CITY, NJ

ELEVATION: 75

TDZE: 63

AIRPORT NAME:

ATLANTIC CITY INTL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Y RWY 31, AMDT 3

23 SEP 2010

SUP: RNAV (GPS) RWY 31

AMDT: 2

DATED: 09/25/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KACY
RUNWAY RW31
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR Y
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W31A
LTP/FTP LATITUDE 392704.9400N
LTP/FTP LONGITUDE 0743335.0900W
LTP/FTP ELLIPSOIDAL HEIGHT -00146
FPAP LATITUDE 392751.3400N
FPAP LONGITUDE 0743527.6500W
THRESHOLD CROSSING HEIGHT (TCH) 00052.4
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0000
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

2EAD9B8F

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +00192
FPAP ORTHOMETRIC HEIGHT +00192

QUALITY
CHECKED

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75 TDZE: 63 AIRPORT NAME: ATLANTIC CITY INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 31, AMDT 3 23 SEP 2010	SUP. RNAV (GPS) RWY 31
				AMDT: 2
				DATED: 09/25/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75	TDZE: 63	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP. RNAV (GPS) RWY 31
	AIRPORT NAME:			RNAV (GPS) Y RWY 31, AMDT 3	AMDT: 2
	ATLANTIC CITY INTL			23 SEP 2010	DATED: 09/25/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

03780060 + 02000

A JS

[illegible]

SUSAP KACYK6GRW31 0100003080 N39270494W074333509+0100 -0014600063000052150I

[illegible]

SUSAP KACYK6PR31-Y RW31 001Y0000W31A0N3927049400W07433350900-001460300N3927513400W07435276500106750000000524F4003502EAD9B8F

SUSAP KACYK6PR31-Y RW31 002E +00192+00192LPV 50113

[illegible]

SUSAP KACYK6SRW31 K6PG 0 18018002125

M

QUALITY
4
CHECKED

ELEVATION: 75 TDZE: 63
AIRPORT NAME:
ATLANTIC CITY INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Y RWY 31, AMDT 3
23 SEP 2010

SUP:	RNAV (GPS) RWY 31
AMDT:	2
DATED:	09/25/2008