

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
SIYPO (IAF)	CODRA (NOPT) (FB)	007.04 / 5.00	2400	LNAV: RW28 CLIMBING LEFT TURN TO 2400 DIRECT CODRA AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 258 WSK ON OL TWR 174249N/06444559W CHART 268 STACKS 2 174242N/0644455W. CHART VDP AT 1.42 MILES TO RW28. HIVOD TO RW28: 3.06/55.
LACEC (IAF)	CODRA (NOPT) (FB)	187.04 / 5.00	2400	
CODRA (IF/IAF)	HIVOD (FB)	277.04 / 6.04	2400	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E CODRA, RT, 277.04 INBOUND, 2400 FT. IN LIEU OF PT (IAF)
- FAC: 277.01 FAF: HIVOD DIST FAF TO MAP: 7.14 THLD: 7.14
- MIN. ALT: CODRA 2400, HIVOD 2400, JOMBI/4.50 NM TO RW28 1520, FEGIR/2.30 NM TO RW28 800
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 13W

EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	560	1	520	560	1	520	560	1 1/2	520	560	1 3/4	520			
CIRCLING	560	1	486	560	1	486	560	1 1/2	486	640	2	566			

NOTES:
CHART NOTE: CIRCLING NA N OF RWY 10-28.
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA.

CITY AND STATE CHRISTIANSTED, ST CROIX, VI	ELEVATION: 74 TDZE: 40 AIRPORT NAME: HENRY E ROHLSEN	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 28, AMDT 1 18 DEC 2008	SUP: AMDT: ORIG DATED 11/25/2004
---	--	---------------------------------	--	--



RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	187/30 CW 007/30 (NOPT)	CODRA (IF/IAF) (FB)	2400
2.	007/30 CW 097/30	SIYPO (IAF) (FB)	2700
3.	097/30 CW 187/30	LACEC (IAF) (FB)	2700

CITY AND STATE

CHRISTIANSTED, ST CROIX, VI

ELEVATION: 74

TDZE: 40

AIRPORT NAME:

HENRY E ROHLSSEN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 28, AMDT 1

18 DEC 2008

SUP:

AMDT:

ORIG

DATED: 11/25/2004

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	ORIG
DATED:	11/25/2004

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	CODRA	CODRA	010		HF	R	FB		277.0(264T)	004.0	02400
	LACEC	LACEC	010	IAF	IF		FB				
	LACEC	CODRA	020		TF		FB	1.0	187.0(174T)	005.0	02400
	SIYPO	SIYPO	010	IAF	IF		FB				
	SIYPO	CODRA	020		TF		FB	1.0	007.0(354T)	005.0	02400
		CODRA	010	FACF	IF		FB				02400
		HIVOD	020	FAF	TF		FB	0.5	277.0(264T)	006.0	02400
		JOMBI	021	SDF	TF		FB	0.3	277.0(264T)	002.6	01520
		FEGIR	022	SDF	TF		FB	0.3	277.0(264T)	004.8	00800
		RW28	030	MAP	TF		FO	0.3	277.0(264T)	002.3	00082

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	CODRA	040		DF	L	FO	1.0			02400
	CODRA	050		HM	R	FO	2.0	277.0(264T)	004.0	02400

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CODRA	N174332.48	W0643342.24	N1743.541	W06433.704
	FEGIR	N174224.12	W0644502.13	N1742.402	W06445.036
	HIVOD	N174254.60	W0643959.83	N1742.910	W06439.997
	JOMBI	N174238.00	W0644244.62	N1742.633	W06442.744
	LACEC	N174832.05	W0643414.89	N1748.534	W06434.248
	SIYPO	N173832.91	W0643309.62	N1738.549	W06433.160
	RW28	N174209.58	W0644725.89	N1742.160	W06447.432

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW28	00027	55

CITY AND STATE
 CHRISTIANSTED, ST CROIX, VI

ELEVATION: 74 TDZE: 40
 AIRPORT NAME:
 HENRY E ROHLSSEN

FACILITY
 IDENTIFIER:
 RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 28, AMDT 1
 18 DEC 2008

SUP:
 AMDT: ORIG
 DATED: 11/25/2004

