

**Federal Aviation
Administration**

Transmittal Letter 21-18

JULY 9, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/12/2021	OH	Wooster	Wayne County	1/6035	6/25/2021	RNAV (GPS) RWY 10, Orig

AIRAC Date: 12 AUGUST 2021

FDC 1/6035 BJJ IAP WAYNE COUNTY, WOOSTER, OH. RNAV (GPS) RWY 10, ORIG...
CIRCLING CAT B MDA 1700/HAA 564, CAT C MDA 1800/HAA 664, CAT D MDA 1840/HAA
704. VIS CAT C 1 3/4, CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE AKRON-CANTON RGNL ALTIMETER SETTING AND
INCREASE ALL MDA 60 FEET AND VISIBILITY CIRCLING CAT C/D 1/4 SM. ALTERNATE
MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4; NA WHEN LOCAL WEATHER NOT
AVAILABLE. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT
(VGSI ANGLE {ANGLE}/TCH {FEET}). THIS IS RNAV (GPS) RWY 10, ORIG-A. 2106171821-
PERM