

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW26 CLIMBING RIGHT TURN TO 2800 DIRECT SN NDB AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2800. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 216.00 INBOUND. CHART FAS OBST: 493 TREE 150049N/1453939E CHART APT ELEV: 271 CHART VDP AT 1.40 MILES TO RW26. CHART TDZE: 271 DUCFI TO RW26 3.04/45.
SNAPP	SHODA (FB)	227.24 / 63.63	4700	
HIRCH	GAFWY (FB)	078.01 / 4.28	7000	
GAFWY (IAF)	SADVE (FB)	353.43 / 14.02	2600	
SHODA (IAF)	SADVE (FB)	163.96 / 6.58	2600	
SADVE (IF)	DUCFI (FB)	258.10 / 6.40	1800	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT SADVE
3. FAC: 258.07 FAF: DUCFI DIST FAF TO MAP: 4.60 THLD: 4.60
4. MIN. ALT: SADVE 2600, DUCFI 1800
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS CLEAR
8. MSA FROM: RW26 2800

MAG VAR: 1E

EPOCH YEAR: 2005

MINIMUMS															
TAKEOFF:	STANDARD	☒	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: NA	STANDARD @										
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	760	1	489	760	1	489	760	1 1/4	489	760	1 1/2	489			
CIRCLING	760	1	489	760	1	489	800	1 1/2	529	960	2 1/4	689			

SAIPAN ALTIMETER SETTING MINIMUMS															
LNAV MDA	780	1	509	780	1	509	780	1 1/2	509	780	1 1/2	509			
CIRCLING	800	1	529	800	1	529	840	1 1/2	569	1000	2 1/4	729			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE SAIPAN ALTIMETER SETTING.
CHART NOTE: VDP NA WHEN USING SAIPAN ALTIMETER SETTING.

@ CAT D 800-2 1/4
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE TINIAN ISLAND, CQ	ELEVATION: 271 TDZE: 271 AIRPORT NAME: TINIAN INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, AMDT 1 27 AUG 2009	SUP:
				AMDT: ORIG
				DATED 10/30/2003



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	ORIG
DATED:	10/30/2003

003
QUALITY
2
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	HIRCH	HIRCH	010		IF		FB				
	HIRCH	GAFWY	020	IAF	TF		FB	2.0	078.0(079T)	004.3	07000
	HIRCH	SADVE	030		TF		FB	1.0	353.4(354T)	014.0	02600
	SNAPP	SNAPP	010		IF		FB				
	SNAPP	SHODA	020	IAF	TF		FB	2.0	227.2(228T)	063.6	04700
	SNAPP	SADVE	030		TF		FB	1.0	164.0(165T)	006.6	02600
		SADVE	010	FACF	IF		FB				02600
		DUCFI	020	FAF	TF		FB	0.5	258.1(259T)	006.4	01800
		RW26	030	MAP	TF		FO	0.3	258.1(259T)	004.6	00316

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	SN	040		DF	R	FO	1.0			02800
	SN	050		HM	R	FO	2.0	216.0(217T)	004.0	02800

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	SN	N150641.20	E1454237.20	N1506.687	E14542.620
	DUCFI	N150057.85	E1454232.86	N1500.964	E14542.548
	GAFWY	N144810.20	E1455026.77	N1448.170	E14550.446
	HIRCH	N144721.11	E1454606.68	N1447.352	E14546.111
	SADVE	N150210.84	E1454902.34	N1502.181	E14549.039
	SHODA	N150833.70	E1454716.47	N1508.562	E14547.275
	SNAPP	N155112.38	E1463620.82	N1551.206	E14636.347
	RW26	N150005.22	E1453752.74	N1500.087	E14537.879

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW26	00271	45

CITY AND STATE TINIAN ISLAND, CQ	ELEVATION: 271 TDZE: 271	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, AMDT 1 27 AUG 2009	SUP:
	AIRPORT NAME: TINIAN INTL			AMDT: ORIG
				DATED: 10/30/2003

QUALITY
2
CHECKED