

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
FLIBB	MOMDE (FO)	352.56 / 21.18	2400	LNAV: RW17
HFD VOR/DME (IAF)	MOMDE (NOPT) (FB)	212.44 / 5.29	2400	CLIMB TO 2100 DIRECT AKIJE AND VIA TRACK 168.38 TO FLIBB AND HOLD.
MOMDE (IF/IAF)	MAPLE (FB)	173.76 / 6.10	2000	
				ADDITIONAL FLIGHT DATA: HOLD S, LT, 348.42 INBOUND. CHART FAS OBST: 709 AAO 412456N/0723102W MAPLE TO RW17: 3.04/40.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **HOLD N MOMDE, LT, 173.76 INBOUND, 2400 FT. IN LIEU OF PT (IAF)**
3. FAC: 173.79 FAF: MAPLE DIST FAF TO MAP: 4.83 THLD: 4.83
4. MIN. ALT: **MOMDE 2400, MAPLE 2000, OGTEE/2.50 NM TO RW17 1240**
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: **34:1 IS NOT CLEAR**
8. MSA FROM: **RW17 3100**

EPOCH YEAR: 1980

[illegible]

Ⓢ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE CHESTER, CT	ELEVATION: 416 TDZE: 416 AIRPORT NAME: CHESTER	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG 27 AUG 2009	SUP:
				AMDT: NONE
				DATED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE CHESTER, CT	ELEVATION: 416 TDZE: 416 AIRPORT NAME: CHESTER	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG 27 AUG 2009	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
RUNWAY	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KSNCK6GRW17	0027221738	N41230884W072302430+0500	+0091600400055940050R									

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KSNCK6SRW17 K6PG	0	18018003125	M									

QUALITY
1
CHECKED

CITY AND STATE
CHESTER, CT

ELEVATION: 416 TDZE: 416
AIRPORT NAME:
CHESTER

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 17, ORIG
27 AUG 2009

SUP:
AMDT: NONE
DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	FLIBB	FLIBB	010		IF		FB				
	FLIBB	MOMDE	020		TF		FO	2.0	352.6 (340T)	021.2	02400
	FLIBB	MOMDE	030	IAF	HF	L	FO		173.8 (161T)	004.0	02400
	HFD	HFD	010	IAF	IF		FB				
	HFD	MOMDE	020		TF		FB	1.0	212.4 (199T)	005.3	02400
		MOMDE	010	FACF	IF		FB				02400
		MAPLE	020	FAF	TF		FB	0.5	173.8 (161T)	006.1	02000
		OGTEE	021	SDF	TF		FB	0.3	173.8 (161T)	002.3	0124001252
		RW17	030	MAP	TF		FO	0.3	173.8 (161T)	002.5	00440

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	AKIJE	040		DF		FB				
	FLIBB	050		TF		FO		168.4 (155T)		02100
	FLIBB	060		HM	L	FO	2.0	348.4 (335T)	004.0	02100

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HFD	N413827.98	W0723250.70	N4138.466	W07232.845
	AKIJE	N411815.93	W0722809.24	N4118.266	W07228.154
	FLIBB	N411337.34	W0722520.19	N4113.622	W07225.337
	MAPLE	N412742.87	W0723231.10	N4127.715	W07232.518
	MOMDE	N413328.42	W0723511.43	N4133.474	W07235.191
	OGTEE	N412530.57	W0723129.84	N4125.510	W07231.497
	RW17	N412308.84	W0723024.30	N4123.147	W07230.405

RUNWAY DATA	THRESHOLD	ELEVATION	TCH
RWY			
RW17	00400		40

QUALITY
CHECKED

CITY AND STATE
CHESTER, CT

ELEVATION: 416 TDZE: 416
 AIRPORT NAME:
 CHESTER

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 17, ORIG
 27 AUG 2009

SUP:
 AMDT: NONE
 DATED: