

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
GUBFO (IF/IAF)	IMOXY (FB)	359.04 / 7.00	1900	LPV: DA LNAV/VNAV: DA LNAV: RW36	
IMOXY (FAF)	WOLSO/1.50 NM TO RW36 (FB)	359.04 / 3.47	2700	CLIMB TO 2700 DIRECT EYPEB AND HOLD.	
WOLSO/1.50 NM TO RW36	RW36 (MAP) (FO)	359.04 / 1.50			
RW36 (MAP)	472 MSL	359.04			
472 MSL	EYPEB (FO)				
<p style="color: red;">This is a corrected copy of this procedure published in TL 11-20. Page 4, the AIRINC, page was not published in TL 11-20.</p>				ADDITIONAL FLIGHT DATA: HOLD N, RT, 179.04 INBOUND. CHART FAS OBST: 391 TANK 360722N/0905607W DISTANCE TO THLD FROM 200 HATH: 0.49 NM. WAAS CHANNEL # 45825 REFERENCE PATH ID: W36A LTP HAE: 54.9 M	

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD S GUBFO, RT, 359.04 INBOUND, 3100 FT. IN LIEU OF PT (IAF)
3. FAC: 359.04 FAF: IMOXY DIST FAF TO MAP: 4.97 THLD: 4.97
4. MIN. ALT: GUBFO 3100, IMOXY 1900, WOLSO/1.50 NM TO RW36 780*
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 1900 GS ALT AT: IMOXY 1900 OM: MM: IM:
7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR
8. MSA FROM:

MAG VAR: 1E EPOCH YEAR: 2000

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	472	1	200	472	1	200	472	1	200	472	1	200			
LNAV/VNAV DA	572	1	300	572	1	300	572	1	300	572	1	300			
LNAV MDA	660	1	388	660	1	388	660	1 1/8	388	660	1 1/8	388			
CIRCLING	760	1	481	760	1	481	760	1 1/2	481	840	2	561			

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING JONESBORO ALTIMETER SETTING. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 42C (107F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 *LNAV ONLY
 (SEE FORM 8260-10)

CITY AND STATE WALNUT RIDGE, AR	ELEVATION: 279 THRE: 272	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDТ NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDТ 1 20 OCT 2011	SUP:
	AIRPORT NAME: WALNUT RIDGE RGNL			AMDT: ORIG-A
				DATED 08/28/2008

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE ALL DA 54 FEET AND ALL MDA 60 FEET; INCREASE LPV ALL CATS AND LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE AND LNAV CAT C AND D VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	269/30 CW 089/30 (NOPT)	GUBFO (IAF) (FB)	3100
2.	089/30 CW 269/30	GUBFO (IAF) (FO)	3100

CITY AND STATE
WALNUT RIDGE, AR

ELEVATION: 279 THRE: 272
 AIRPORT NAME:
WALNUT RIDGE RGNL

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 36, AMDT 1
 20 OCT 2011

SUP:
 AMDT: **ORIG-A**
 DATED: **08/28/2008**

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KARG
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	360708.3910N
LTP/FTP LONGITUDE	0905523.8100W
LTP/FTP ELLIPSOIDAL HEIGHT	+00549
FPAP LATITUDE	360837.6200N
FPAP LONGITUDE	0905523.7300W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 FD085031

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00830
FPAP ORTHOMETRIC HEIGHT	+00830



CITY AND STATE WALNUT RIDGE, AR	ELEVATION: 279 THRE: 272	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 20 OCT 2011	SUP:
	AIRPORT NAME: WALNUT RIDGE RGNL			AMDT: ORIG-A
				DATED: 08/28/2008

