

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
CUMUL (IAF)	KOKEC (FB)	056.34 / 8.00	2000	LNAV: RW33
HUNOV (IAF)	KOKEC (FB)	236.48 / 8.00	2000	
KOKEC (IF)	ORUDE (FB)	326.41 / 7.00	2000	CLIMB TO 2500 DIRECT NUPSY AND HOLD.
ORUDE (FAF)	WENAB/1.50 NM TO RW33 (FB)	326.38 / 3.51		
WENAB/1.50 NM TO RW33	RW33 (MAP) (FO)	326.37 / 1.50		
RW33 (MAP)	760 MSL	326.37		ADDITIONAL FLIGHT DATA: HOLD NW, RT, 146.30 INBOUND. CHART FAS OBST: 499 POWERLINE 303019N/0964202W ORUDE TO RW33: 3.00/40
760 MSL	NUPSY (FO)		2500	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT KOKEC
- FAC: 326.38 FAF: ORUDE DIST FAF TO MAP: 5.01 THLD: 5.01
- MIN. ALT: KOKEC 2000, ORUDE 2000, WENAB/1.50 NM TO RW33 880
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW33 2300

MAG VAR: 6E EPOCH YEAR: 1990

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	760	1	395	760	1	395		NA			NA				
CIRCLING	1000	1	609	1000	1	609		NA			NA				

NOTES:
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLLEGE STATION ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: CIRCLING NA EAST OF RWY 15-33.
 CHART NOTE: DME/DME RNP-0.3 NA.
 (SEE FORM 8260-10)



CITY AND STATE CALDWELL, TX	ELEVATION: 391 THRE: 365 AIRPORT NAME: CALDWELL MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 33, ORIG 20 SEPTEMBER 2012	SUP: AMDT: NONE DATED
--------------------------------	--	------------------------------	--	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: RADAR REQUIRED.

QUALITY
CHECK

CITY AND STATE

CALDWELL, TX

ELEVATION: 391

THRE: 365

AIRPORT NAME:

CALDWELL MUNI

FACILITY IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 33, ORIG

20 SEPTEMBER 2012

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	CUMUL	CUMUL	010	IAF	IF		FB					
	CUMUL	KOKEC	020		TF		FB	1.0	056.3 (062.3T)	008.0	AA 02000	
	HUNOV	HUNOV	010	IAF	IF		FB					
	HUNOV	KOKEC	020		TF		FB	1.0	236.5 (242.5T)	008.0	AA 02000	
		KOKEC	010	FACF	IF		FB				AA 02000	
		ORUDE	020	FAF	TF		FB	0.5	326.4 (332.4T)	007.0	AA 02000	
		WENAB	021	SDF	TF		FB	0.3	326.4 (332.4T)	003.5	AA 00880	GS 00882
		RW33	030	MAP	TF		FO	0.3	326.4 (332.4T)	001.5	AT 00405	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		326.4 (332.4T)		AA 00760	
	NUPSY	050		DF		FO				AA 02500	
	NUPSY	060		HM	R	FO		146.3 (152.3T)	004.0	AA 02500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CUMUL	N301620.51	W0964352.36	N3016.342	W09643.873
	HUNOV	N302346.18	W0962729.17	N3023.770	W09627.486
	KOKEC	N302003.60	W0963541.08	N3020.060	W09635.685
	NUPSY	N304145.92	W0964848.95	N3041.765	W09648.816
	ORUDE	N302616.67	W0963926.08	N3026.278	W09639.435
	WENAB	N302923.65	W0964119.05	N3029.394	W09641.318
	RW33	N303043.57	W0964207.37	N3030.726	W09642.123

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW33	00365	40



CITY AND STATE CALDWELL, TX	ELEVATION: 391	THRE: 365	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 33, ORIG 20 SEPTEMBER 2012	SUP:
	AIRPORT NAME: CALDWELL MUNI		RNAV		AMDT: NONE
					DATED: