

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
BAE VOR/DME	RYV NDB	278.13 / 19.66	2500

MAP: RYV NDB

CLIMB TO 2500 THEN RIGHT TURN DIRECT RYV NDB AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD SW, RT, 039.00 INBOUND.
CHART FAS OBST: 1089 TOWER 430521N/0884529W.
FAC CROSSES RWY C/L EXTENDED 3000 FT FROM THLD.

- PT L SIDE OF COURSE 219.00 OUTBOUND 2500 FT WITHIN 10 MILES OF RYV NDB (IAF)
-
- FAC 039.00 FAF _____ DIST FAF TO MAP _____ THLD _____
- MIN. ALT _____
- MSA FROM: **RYV NDB 2700**

MAG VAR: **1W** EPOCH YEAR: **1990**

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-05	1460	1	639	1460	1	639	1460	1 3/4	639	1460	2	639				
CIRCLING	1460	1	627	1460	1	627	1460	1 1/2	627	1720	3	887				

NOTES:
CHART NOTE: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART NOTE: STRAIGHT-IN RWY 5 NA AT NIGHT, CIRCLING RWY 5, 23 NA AT NIGHT.



CITY AND STATE WATERTOWN, WI	ELEVATION: 833 TDZE: 821 AIRPORT NAME: WATERTOWN MUNI	FACILITY IDENTIFIER: RYV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 5, AMDT 1E 1 MARCH 2018	SUP AMDT 1D DATE 10/12/2017
--	--	------------------------------------	---	---