

file

DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION <u>NDB</u> STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. <u>27</u>	Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	--

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALT	MAP: 2.7 miles after MOG NDB Climbing right turn to 6800 direct MOG NDB and hold.
FJS VORTAC	MOG NDB	022/22.2	8500	ADDITIONAL FLIGHT DATA Hold SE, RT, 337 inbound FAS Obst: 2915 beacon 414505/1222914
LMT VORTAC	MOG NDB	214/42.4	10000	

1. PT <u>L</u> SIDE OF CRS <u>157</u> OUTBND, <u>6800</u> FT WITHIN <u>10</u> MI. OF <u>MOG NDB</u> (IAF) 2. _____ 3. FAC <u>352</u> FAF <u>MOG NDB</u> DIST FAF TO: MAP <u>2.7</u> THLD <u>2.7</u> 4. MIN ALT <u>MOG NDB 4800</u> 5. MSA FROM <u>MOG NDB 015-105 9600, 105-195 15200, 195-285 9300, 285-015 8600</u>	VAR 19E YR 75
---	---------------

MINIMUMS															
TAKEOFF: ☐ STD ☒ SEE FAA FORM 8260-15 FOR THIS AIRPORT	ALTERNATE: ☐ NA														
CAT. →	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
Circling	3760	1 1/4	1112	3760	1 1/2	1112	3760	3	1112	3760	3	1112			

NOTES

 Use Siskiyou County altimeter setting; when not available, use Yreka-Rohrer Field altimeter setting; when neither received, procedure NA.

CITY AND STATE	ELEVATION AIRPORT	TDZE	FACILITY IDENT.	PROC. NO.-AMD. NO.-EFFECTIVE DATE	SUP.
Montague, CA	2648		MOG	5 APR 90 NDB-A Amdt. 7	AMD 6 DATED 15 JAN 87