

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 19, 500-3 OR STANDARD WITH MINIMUM CLIMB OF 253 FT PER NM TO 1300.

RWY 01, 500-3 OR STANDARD WITH MINIMUM CLIMB OF 385 FT PER NM TO 1200.

RWY 9, NA - OBSTACLES.

RWY 27, NA - OBSTACLES.

(2) DEPARTURE PROCEDURE:

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 19, ROAD 23' FROM DER, ON CENTERLINE, 15' AGL/599' MSL.

NOTE: RWY 01, MULTIPLE TREES BEGINNING 5,364' FROM DER, 180' RIGHT OF CENTERLINE UP TO 100' AGL/915' MSL. MULTIPLE TREES BEGINNING 5,596' FROM DER, 1,180' LEFT OF CENTERLINE UP TO 100' AGL/909' MSL. MULTIPLE TREES BEGINNING 1.5 NM FROM DER, 2,293' LEFT OF CENTERLINE UP TO 200' AGL/849' MSL.

(4) CONTROLLING OBSTACLES:

RWY 19: 1055 MSL TOWER 391252.00N/0844543.00W

RWY 01: 999 MSL TREE 391808.69N/0844647.24W, 919 MSL TREE 391656.80N/0844623.73W

(5) City, State

HARRISON, OHIO

(6) Airport

CINCINNATI WEST

(7) Effective Date

JUL -5 2007

(8) Amdt. No.

2

