

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: KUKUI	
TAMMI (IAF)	CORGA (FB)	128.81 / 14.18	4300	CLIMB TO 5000 DIRECT LICEP AND ON TRACK 057.04 TO TIGAH AND HOLD.	
MYNAH (IAF)	CORGA (FB)	052.83 / 13.50	4300		
CORGA (IF)	KONEA (FB)	054.92 / 7.28	4300		
KONEA (FAF)	KUKUI (MAP) (FO)	054.96 / 4.52			
KUKUI (MAP)	3071 MSL	054.96		ADDITIONAL FLIGHT DATA: HOLD NE, RT, 237.04 INBOUND. CHART FAS OBST: 2694 TREE 200003N/1554034W CHART VDP AT 1.46 MILES TO KUKUI. FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD. KONEA TO RW04: 3.00/45	
3071 MSL	LICEP (FB)				
LICEP	TIGAH (FO)	057.04 / 10.41	5000		
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)					
2. PROFILE STARTS AT CORGA					
3. FAC: <u>054.96</u> FAF: <u>KONEA</u> DIST FAF TO MAP: <u>4.48</u> THLD: <u>4.97</u>					
4. MIN. ALT: CORGA 4300, KONEA 4300					
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>					
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>					
7. GS ANGLE: <u> </u> TCH: 34:1 IS CLEAR					
8. MSA FROM: KUKUI 15000					
MAG VAR: 11E EPOCH YEAR: 1985					
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A X		
CATEGORY ==>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	3220	1	558	3220	1
CIRCLING	3520	1 1/4	849	3520	1 1/4
NOTES: CHART NOTE: CIRCLING NA NW OF RWY 4-22. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.					
CITY AND STATE KAMUELA, HI		ELEVATION: 2671 THRE: 2662 AIRPORT NAME: WAIMEA-KOHALA		FACILITY IDENTIFIER: RNAV	
				PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1, 08/25/2011 25 AUG 2011	
				SUP: AMDT: ORIG-A DATED 08/30/2007	

QUALITY
 A
 CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

QUALITY
CHECKED

SUP:	
AMDT:	ORIG-A
DATED:	08/30/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

RECEIVED

CITY AND STATE KAMUELA, HI	ELEVATION: 2671 THRE: 2662 AIRPORT NAME: WAIMEA-KOHALA	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 25 AUG 2011	SUP:
				AMDT: ORIG-A
				DATED: 08/30/2007