US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
POCIT	NUCLA (TF) (FB) (RNP 2.00)	003.94 / 17.69	8800
DSD VORTAC	AWBAN (TF) (FO) (RNP 2.00)	097.94 / 20.78	7600
NUCLA (IAF)	AWBAN (NOPT) (TF) (FB) (RNP 1.00)	004.04 / 9.00	7600
FUFQO (IAF)	AWBAN (NOPT) (TF) (FB) (RNP 1.00)	273.03 / 8.29	7600
AWBAN (IF/IAF)	COLTA (TF) (FB) (RNP 1.00)	288.09 / 7.18	6300
(SEE FORM 8260-10)			

THIS IS A CORRECTED COPY OF A FORM ORIGINALLY PUBLISHED IN TL 18-01.

MISSED APPROACH

LPV: DA
LNAV/VNAV: DA

CLIMB TO 4000 THEN CLIMBING RIGHT TURN TO 7000 DIRECT YONKU AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000.

ADDITIONAL FLIGHT DATA:
HOLD N, RT, 167.55 INBOUND.
DISTANCE TO THLD FROM 286 HAT: 0.76 NM.
WAAS CHANNEL # 90214
REFERENCE PATH ID: W29A
LTP HAE: 917.8 M

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD E AWBAN, RT, 288.09 INBOUND, 7600 FT. IN LIEU OF PT (IAF)
3. FAC: 288.00 FAF: ← DIST FAF TO MAP: 7.12 THLD: 7.12
4. MIN. ALT: AWBAN 7600, COLTA 6300
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: 6300 GS ALT AT: COLTA 6300 OM: ____ MM: ____ IM: ____
7. GS ANGLE: 4.20 TCH: 43.0 34:1 IS CLEAR
8. MSA FROM: RW29 11600

MAG VAR: 14E EPOCH YEAR: 2020

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT | ALTERNATE: N A | STANDARD

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	3366	1	286	3366	1	286		NA			NA				
LNAV/VNAV DA	3366	1	286	3366	1	286		NA			NA				

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -20C (-4F) OR ABOVE 43C (110F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON DSD VORTAC RADIALS 030 CW 181.
(CONTINUED ON PAGE 2)

QUALITY 35 CHECKED

CITY AND STATE	ELEVATION: 3080 TDZE: 3080 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
REDMOND, OR	ROBERTS FIELD	RNAV	RNAV (GPS) Z RWY 29, AMDT 1A 1 FEBRUARY 2018	AMDT: 1 DATED 08/20/2015

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT , HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
COLTA (FAF)	RW29 (MAP) (TF) (FO) (RNP 0.30)	288.00 / 7.12	
RW29 (MAP)	4000 MSL (CA)	288.00	4000
4000 MSL	YONKU (DF) (FO) (RNP 1.00)		7000

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT POCIT ON V165 SOUTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FUFQO ON V269 EASTBOUND.

QUALITY 16 CHECKED

CITY AND STATE	ELEVATION: 3080 TDZE: 3080	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
REDMOND, OR	AIRPORT NAME: ROBERTS FIELD	RNAV	RNAV (GPS) Z RWY 29, AMDT 1A 1 FEBRUARY 2018	AMDT: 1 DATED: 08/20/2015

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT , HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRDM
RUNWAY	RW29
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Z
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W29A
LTP/FTP LATITUDE	441455.5995N
LTP/FTP LONGITUDE	1210818.5275W
LTP/FTP ELLIPSOIDAL HEIGHT	+09178
FPAP LATITUDE	441542.6615N
FPAP LONGITUDE	1211003.7805W
THRESHOLD CROSSING HEIGHT (TCH)	00043.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	04.20
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0616
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
CRC REMAINDER	D4ADE78D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K1
LTP ORTHOMETRIC HEIGHT	+09388
FPAP ORTHOMETRIC HEIGHT	+09388

QUALITY 16 CHECKED