

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ORL VORTAC (IAF)	WERPO (FB)	242.61 / 12.58	2000	LPV: DA LNAV/VNAV: DA LNAV: RW15 CLIMB TO 2200 DIRECT YARTU AND ON TRACK 221.44 TRACK TO TEMPE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, LT, 025.00 INBOUND. CHART FAS OBST: 232 TOWER 281824N/0812622W CHART FAS OBST: 265 TOWER 281846N/0812745W 294 AAO 282020N/0812934W. DISTANCE TO THLD FROM 200 HAT: 0.48 NM. CHART VDP AT 1.22 MILES TO RW15* *LNAV ONLY. WAAS CHANNEL # 45507 REFERENCE PATH ID: W15A
JENSN (IAF)	WERPO (FB)	071.67 / 13.12	2000	
WERPO (IF)	WADSI (FB)	153.03 / 6.10	1200	

- PT NA SIDE OF COURSE OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- PROFILE STARTS AT WERPO
- FAC: 153.06 FAF: WADSI DIST FAF TO MAP: 3.33 THLD: 3.33
- MIN. ALT: WERPO 2000, WADSI 1200
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: 1200 GS ALT AT: WADSI 1200 OM: _____ MM: _____ IM: _____
- GS ANGLE: 3.00 TCH: 50.8 34:1 IS CLEAR
- MSA FROM: RW15 3000

MAG VAR: 5W EPOCH YEAR: 2000

MINIMUMS																
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A	STANDARD @					
CATEGORY	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	282	3/4	200	282	3/4	200	282	3/4	200	282	3/4	200				
LNAV/VNAV DA	532	1 1/2	450	532	1 1/2	450	532	1 1/2	450	532	1 1/2	450				
LNAV MDA	520	3/4	438	520	3/4	438	520	1 1/4	438	520	1 1/2	438				
CIRCLING	680	1	598	680	1	598	680	1 1/2	598	680	2	598				

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VDP AND BARO-VNAV NA WHEN USING ORLANDO INTL ALTIMETER SETTING.
 CHART PLANVIEW NOTES: PROCEDURE NA FOR ARRIVALS AT ORL VORTAC ON V533 NORTHEAST BOUND AND AT JENSN
 SEE 8260-10

CITY AND STATE ORLANDO, FL	ELEVATION: 82 TDZE: 82 AIRPORT NAME: KISSIMMEE GATEWAY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 15, AMDT 1 26 AUG 2010	SUP: AMDT: ORIG DATED 11/23/2006
--------------------------------------	---	------------------------------	--	--